# AIR FORCE INSTITUTE OF TECHNOLOGY

AIR UNIVERSITY
UNITED STATES AIR FORCE

SCHOOL OF ENGINEERING

D D C

APR 27 1978

A

WRIGHT-PATTERSON AIR FORCE BASE, OHIO

THE DESIGN AND SIMULATION OF A TAKEOFF STABILIZATION

SYSTEM FOR AN AIRCRAFT WITH AN AIR CUSHION LANDING SYSTEM

THESIS

GE/EE/77D-43   Edward A. Kenney
                                            Captain   CAF

Approved for Public Release; Distribution Unlimited.

D D C

APR 27 1978

A

THE DESIGN AND SIMULATION OF A TAKEOFF STABILIZATION
SYSTEM FOR AN AIRCRAFT WITH AN AIR CUSHION LANDING SYSTEM

THESIS

Presented to the Faculty of the School of Engineering

of the Air Force Institute of Technology

Air University

in Partial Fulfillment of the

Requirements for the Degree of

Master of Science

by

Edward A. Kenney, B.Sc.

Captain   CAF

Graduate Electrical Engineering

December 1977

Preface

When the Air Cushion System replaced the conventional takeoff
and landing systems of the Jindivik remotely piloted vehicle, the
possibility existed that instabilities in pitch, roll, and yaw
could occur. As a result, this paper was intended as a design
of a Takeoff Stabilization System for the Jindivik using existing
autopilot sensors and incorporating an engine yaw thruster and
vertical wing tip roll thrusters. When the design was completed,
it was sufficiently general that the technique could be applied
to any air cushion aircraft or VTOL aircraft. The Landing Sta-
bilization System for the Jindivik using the same sensors and
actuators is presently being designed by Captain Max Stafford
as his thesis for the Air Force Institute of Technology (AFIT).

I wish to express my gratitude to my Thesis advisors, Dr.
George Kurylowich of the Air Force Flight Dynamics Laboratory
(AFFDL) and Major R. Potter of AFIT. Also, thanks are due to
Captain James Negro of AFIT, Major Jack Randall and Mr. Jim
Steiger of the Air Force Flight Dynamics Laboratory for their
technical advice and assistance.

My wife, Jane, does not know how much she has contributed
to this study, but her patience, understanding, and encouragement
has definitely made the past eighteen months of work much easier.

Edward Kenney

AFIT/GE/EE/77D-43

Contents

List of Figures

List of Tables

List of Symbols

All symbols are in ft-lb-sec units unless indicated to the contrary.

Alphanumeric Symbols

Symbol		Definition
A		Area
AR	$= \dfrac{b^2}{S}$	Aspect Ratio
a		Horizontal distance between the inner and outer trunk attachment points
b		Wing span
c		Wing chord
C_D	$= \dfrac{D}{\bar{q} S}$	Drag coefficient
C_{DO}		Drag coefficient for zero angle of attack and zero elevator angle
$C_{D\alpha}$	$= \dfrac{\partial C_D}{\partial \alpha}$	Variation of drag coefficient with angle of attack
CG		Centre of gravity (of aircraft)
C_L	$= \dfrac{L}{\bar{q} S}$	Lift coefficient

Symbol		Definition
C_{Lo}		Lift coefficient for zero angle of attack and zero elevator angle
C_{Lq}	$= \dfrac{2U}{C} \dfrac{\partial C_L}{\partial q}$	Variation of lift coefficient with pitch rate
C_{Lt}		Coefficient of lift of the tail
$C_{L\alpha}$	$= \dfrac{\partial C_L}{\partial \alpha}$	Aircraft lift curve slope
$C_{L\alpha_F}$		Lift curve slope of the vertical stabilizer
$C_{L\alpha_t}$		Lift curve slope of the horizontal stabilizer
$C_{L\alpha_{2-D}}$		Theoretical two dimensional lift-curve slope of an airfoil at $0°$ absolute
$C_{L\dot{\alpha}}$	$= \dfrac{2U}{C} \dfrac{\partial C_L}{\partial \dot{\alpha}}$	Variation of lift coefficient with rate of change of angle of attack
C_ℓ	$= \dfrac{\gamma}{\bar{q}Sb}$	Rolling moment coefficient
C_{ℓ_P}	$= \dfrac{2U}{b} \dfrac{\partial C_L}{\partial P}$	Variation of rolling moment coefficient with roll rate

Symbol		Definition
C_{ℓ_r}	$= \dfrac{2U}{r}\dfrac{\partial C_L}{\partial r}$	Variation of rolling moment coefficient with yaw rate
C_{ℓ_β}	$= \dfrac{\partial C_L}{\partial \beta}$	Variation of rolling moment coefficient with sideslip angle
C_m	$= \dfrac{m}{\bar{q}Sc}$	Pitching moment coefficient
C_{m_q}	$= \dfrac{2U}{c}\dfrac{\partial C_m}{\partial q}$	Variation of pitching moment coefficient with pitch rate
$C_{m_{\dot\alpha}}$	$= \dfrac{2U}{c}\dfrac{\partial C_m}{\partial \dot\alpha}$	Variation of pitching moment coefficient with rate of change of angle of attack
C_n	$= \dfrac{n}{\bar{q}Sb}$	Yawing moment coefficient
C_{n_p}	$= \dfrac{2U}{b}\dfrac{\partial C_n}{\partial p}$	Variation of yawing moment coefficient with roll rate
C_{n_β}	$= \dfrac{\partial C_n}{\partial \beta}$	Variation of yawing moment coefficient with sideslip angle
C_y	$= \dfrac{F_y}{\bar{q}S}$	Side force coefficient
C_{y_F}		Side force coefficient for the vertical stabilizer

Symbol		Definition
C_{yp}	$= \dfrac{2U}{b} \dfrac{\partial C_y}{\partial p}$	Variation of side force coefficient with roll rate
C_{yr}	$= \dfrac{2U}{b} \dfrac{\partial C_y}{\partial r}$	Variation of side force coefficient with yaw rate
$C_{y\beta}$	$= \dfrac{\partial C_y}{\partial \beta}$	Variation of side force coefficient with sideslip angle
D		Drag
d		Distance between trunk inner attachment points
F		Force
F_{Ax}		Aerodynamic force in the x direction
F_{Ay}		Aerodynamic force in the y direction
F_{Az}		Aerodynamic force in the z direction
F_{cT}		Trunk damping force
F_T		Force from the roll thrusters

Symbol	Definition
F_x	Force in the x direction
$F_{x_{EXT}}$	External force in the x direction
F_y	Force in the y direction
$F_{y_{EXT}}$	External force in the y direction
F_{y_T}	Force from the yaw thrusters
F_z	Force in the z direction
$F_{z_{EXT}}$	External force in the z direction
g	Acceleration due to gravity
H_w	Distance between the ground tangent points on the sides of the trunk
H_y	Height of trunk cross section
i	Incidence angle of the horizontal stabilizer

Symbol	Definition
I_{xx}	Roll moment of inertia of the aircraft about the CG
I_{xz}	Product of inertia of the aircraft about the CG
I_{yy}	Pitch moment of inertia of the aircraft about the CG
I_{zz}	Yaw moment of inertia of the aircraft about the CG
k	C_L^2 coefficient from drag polar
L	Lift
L_s	Length of the straight part of the trunk
$\mathcal{L}$	Rolling moment
$\mathcal{L}_A$	Aerodynamic rolling moment
$\mathcal{L}_{EXT}$	External rolling moment
$\mathcal{L}_{THRUSTERS}, \mathcal{L}_T$	Rolling moment of the roll thrusters

Symbol	Definition
ℓ_F	Distance from CG to mean aerodynamic chord of vertical stabilizer
λ_P	Peripheral distance from inner trunk attachment to first row of trunk orifices
ℓ_t	Distance from CG to mean aerodynamic chord of horizontal stabilizer
$\ell_w = \dfrac{b}{2}$	Length of one wing
M	Number of straight trunk segments in one quarter of trunk periphery
m	Mass
$\mathcal{M}$	Pitching moment
$\mathcal{M}_A$	Aerodynamic pitching moment
$\mathcal{M}_{EXT}$	External pitching moment
N	Number of curved trunk segments in one quarter of trunk periphery

Symbol	Definition
N_h	Number of trunk orifices per row
N_r	Number of rows of trunk orifices
n	Yawing moment
n_A	Aerodynamic yawing moment
n_{EXT}	External yawing moment
n_{YT}	Yawing moment produced by yaw thrusters
P, p	1. Roll rate (about x axis) 2. Pressure
P_A	Atmospheric pressure
P_{AV}	Average pressure
P_{CH}	Cushion pressure
P_T	Trunk pressure
Q, q	Pitch rate (about y axis)

Symbol	Definition
$\overline{q}$	Dynamic pressure
R, r	Yaw rate (about z axis)
S	Reference area (wing)
S_F	Vertical stabilizer reference area
S	Horizontal stabilizer reference area
SX	Roll thruster switching curve
SX_{yT}	Yaw thruster switching curve
T	Trunk loop tension force
t	Time
t_o	Initial time
t^*	Final time
U, u	Velocity of CG along x axis

Symbol	Definition
$u(t)$	Control variable
u_{MAX}	Maximum roll control
$u_{YT\,MAX}$	Maximum yaw thruster control
V, v	Velocity of CG along y axis (aircraft)
v_t	Trunk vertical velocity
W, w	Velocity of CG along z axis (aircraft)
X_{CX}	Distance of trunk segment centre from CG along vehicle x axis
y	Distance along wing
Z_{CX}	Distance of trunk segment centre from CG along vehicle y axis
β_F	Mean height of the vertical stabilizer

Greek Symbols

Symbol	Definition
α	Angle of attack of aircraft
α_F	Angle of attack of vertical stabilizer
β	1. Sideslip angle 2. Angle subtended by curved trunk segment from trunk centre of curvature
ϵ	Downwash angle
δ_e	Elevator angle
δ_f	Flap angle
$\delta(i)$	Angle of trunk curved segment from centre of curvature
δ_s	Side excursion of trunk
δ_x	Width of straight trunk segment
λ	Sweep angle of leading edge of wing (or horizontal stabilizer)

Symbol	Definition
Δ	Mathematical symbol meaning a small change
ρ	Air density
θ	Pitch attitude angle
θ_p	Inclination angle of lift and drag vectors
ϕ	Roll angle
ψ	Yaw angle

Abstract

The inherent instability in pitch and roll associated with an Air Cushion Landing System (ACLS) aircraft at low airspeeds was investigated, and a means to aid control in pitch and roll was developed. The control system required the use of vertical wing tip thrusters which provided thrust up or down depending on the control signal (similar to space vehicle thrusters). These thrusters could be activated alternately to control roll angle and roll rate with the use of a bang-bang optimal controller. As well, the thrusters would be set forward of the aircraft centre of gravity and could be activated in tandum to aid in pitch control.

The Jindivik Remotely Piloted Vehicle, an Australian target drone, was fitted with an ACLS and taxi tests showed the instability and need for a stabilization system. Subsequent use of Jindivik wind tunnel and taxi test data served as the basis for the development of the roll/pitch control system presented in this paper. Due to computational problems with the air cushion model of the computer program, the controller designs could not be completely verified; but expected trends in pitch, roll and yaw control were shown.

THE DESIGN OF A TAKEOFF STABILIZATION
SYSTEM FOR AN AIRCRAFT WITH AN AIR CUSHION LANDING SYSTEM

Chapter I

Introduction

In the low speed range of a takeoff roll, the normal air-craft controls are not aerodynamically effective; hence, the pilot must control the heading by differential braking and wait until the ailerons become effective to control roll. During this time, the landing gear dampens most of the pitch and roll oscillations so that the pilot has few corrections to make in the latter part of the takeoff roll. However, when the conventional landing gear is replaced by an Air Cushion Takeoff System (ACTS) the pitch and roll damping is greatly reduced. This paper will use the Jindivik Remotely Piloted Vehicle as an example of an air cushion vehicle that can be controlled in the low speed range with the use of small jet thrusters on the wing tips and a thrust deflector on the tail section.

The Jindivik Remotely Piloted Vehicle (RPV) is an Australian target drone that can be launched and recovered on a runway. At present, the takeoff is accomplished with a takeoff dolly, as shown in Fig. 1, that provides a wing level attitude and directional control. At lift off the Jindivik separates from the dolly and the dolly brakes to a stop. Recovery of the Jindivik is done by landing on a single, four inch wide metal skid attached to the fuselage. Directional control during landing is maintained with the ailerons, the rolling moment thus produced

1

Fig. 1. Jindivik on a Takeoff Dolly

makes the drone ride up onto an edge of the skid and turn in

the direction of the roll. For the last twelve years the

Australian Air Force has used the Jindivik in this configura-

tion with considerable success.

A joint project by the Australian Air Force and the United

States Air Force was initiated in 1972 to incorporate an Air

Cushion Landing System on the Jindivik. The objectives of this

project were to convert the Jindivik to an all-terrain RPV and

to advance air cushion technology. The drone and air cushion

are shown in Fig. 2. Initial low speed taxi tests, completed

in Australia, show that the aircraft fitted with the air cushion

is unstable in roll, pitch, and directional control (yaw) (Ref.

13). Therefore, a Stability Augmentation System (SAS) will have

2

Fig. 2. Jindivik and Air Cushion Landing System

to be designed and incorporated into the autopilot before the

RPV is airworthy.

Since the drone was designed to be launched from a direc-

tionally controlled dolly, it was not designed with a rudder.

Implementation of a rudder during this project would require

extensive structural changes and major changes to the autopilot

and ground control units. Therefore, a yaw thruster was de-

signed and fitted to the rear of the fuselage to direct the

jet exhaust, thus providing a yawing moment. Roll and pitch

control will be provided by a vertical roll thruster on the

front tip of each wing pod. The roll thrusters will be ac-

tivated alternately to control rolling moments and in tandum

to control pitch. Since the roll thrusters are on the tip

3

Fig. 3. Block Diagram of Autopilot and SAS Control Units

of the wing pods, they are approximately six feet ahead of the centre

of gravity of the drone and hence can produce a moment to control

the pitch attitude to some degree. As well, the roll thrusters

can be directed up or down to counteract positive or negative

rolling and pitching moments.

At velocities near fifty knots, the ailerons and flaps be-

come aerodynamically effective and the roll thrusters are phased

out to ensure that the vehicle is not overcontrolled. An addi-

tional advantage of turning off the roll thrusters is that a

smaller gas supply is required for the thrusters. Hence, they

can be used with a gas bottle rather than bleed air from the

engine. This arrangement will greatly reduce the airframe and

engine modifications required for implementation.

4

The stability augmentation system will be designed to use the existing sensors in the autopilot to control the roll and pitch thrusters. The SAS unit will be placed in the feedback control loop between the autopilot and actuators, as shown in Fig. 3.

This thesis is organized in the following manner: Chapter II develops the equations of motion and aerodynamic stability derivatives, Chapter III describes the air cushion model, Chapter IV discusses the controller design, Chapter V contains a description of the computer program and the simulation results, and Chapter VI the conclusions and recommendations.

Chapter II

The Determination and Solution
of the Jindivik Equations of Motion

The following six simultaneous non-linear differential equations fully describe the motion of the Jindivik RPV. The positive sense of the variables is in the direction of the arrows in Fig. 4.

$$m(\dot{U} - VR + WQ) = -mg \sin\Theta + F_{AX} + F_{X_{EXT}} \tag{1}$$

$$m(\dot{V} + UR - WP) = mg \sin\phi \cos\Theta + F_{AY} + F_{Y_{EXT}} \tag{2}$$

$$m(\dot{W} - UQ + VP) = mg \cos\phi \cos\Theta + F_{AZ} + F_{Z_{EXT}} \tag{3}$$

$$I_{xx}\dot{P} - I_{xz}\dot{R} - I_{xz}PQ + (I_{zz} - I_{yy})RQ = \mathcal{L}_A + \mathcal{L}_{EXT} \tag{4}$$

$$I_{yy}\dot{Q} + (I_{xx} - I_{zz})PR + I_{xz}(P^2 - R^2) = \mathcal{M}_A + \mathcal{M}_{EXT} \tag{5}$$

$$I_{zz}\dot{R} - I_{xz}\dot{P} + (I_{yy} - I_{xx})PQ + I_{xz}QR = \mathcal{N}_A + \mathcal{N}_{EXT} \tag{6}$$

The equations are first order in U, V, W, P, Q, and R with the added kinematic relationships.

$$P = \dot{\phi} - \dot{\psi} \sin\Theta \tag{7}$$

$$Q = \dot{\Theta} \cos\phi + \dot{\psi} \cos\Theta \sin\phi \tag{8}$$

$$R = \dot{\psi} \cos\Theta \cos\phi - \dot{\Theta} \sin\phi \tag{9}$$

The assumptions used in the derivation of these equations were: (1) the aircraft is a rigid body, (2) the mass of the aircraft is constant for the duration of the analysis, (3) gravity is constant, (4) the earth is an inertial reference, (5) and there is body axis symmetry about the x-z plane (i.e., $I_{xy} = 0 = I_{yz}$).

Equations (1) to (9) are included in the subroutines of the "EASY Dynamic Analysis Computer Program to Aircraft Modeling"

AFIT/GE/EE/77D-43

Fig. 4. Definitions of Vector Components in the
Equations of Motion

(Ref. 5) which was used to simulate the takeoff motions of the
Jindivik. The inputs required by EASY are the mass, inertias,
geometry of the aircraft, and tne aerodynamic and external forces
acting on the drone. The air cushion system is considered to be
a prime generator of the external forces ana moments (aside from
engine forces and moments) and is described in the next chapter.
The mass, inertias and geometry are readily available from air-
craft blue prints and reference manuals; and the aerodynamic
forces and moments can be computed from wind tunnel model data
and theoretical methods.

The aerodynamic forces and moments can be written as:

$$L = C_L \bar{q} S \tag{10}$$

$$D = C_D \bar{q} S \tag{11}$$

$$F_y = C_y \bar{q} S \tag{12}$$

$$\mathcal{L} = C_\ell \bar{q} S \tag{13}$$

$$\eta = C_n \bar{q} S \tag{14}$$

$$\mathcal{M} = C_m \bar{q} S \tag{15}$$

where

$$C_L = f(u, \alpha, \dot{\alpha}, q, \delta_e, \delta_f) \tag{16}$$

$$C_D = f(u, \alpha, \dot{\alpha}, q, \delta_e, \delta_f) \tag{17}$$

$$C_y = f(\beta, \dot{\beta}, p, r, \delta_A) \tag{18}$$

$$C_\ell = f(\beta, \dot{\beta}, p, r, \delta_A) \tag{19}$$

$$C_n = f(\beta, \dot{\beta}, p, r, \delta_A) \tag{20}$$

$$C_m = f(u, \alpha, \dot{\alpha}, q, \delta_e, \delta_f) \tag{21}$$

The coefficients C_L, C_D, C_y, C_ℓ, C_n, and $\dot{C}_m$
are non-dimensional. By determining the coefficients for every
flight condition, the aerodynamic forces and moments can be cal-
culated and added to the external forces and moments to produce
the aircraft motions. These calculations are done by the EASY
program but the program requires all the aerodynamic stability
derivatives (all the functional relationships which determine
the force and moment coefficients). The remainder of this chap-
ter will deal with the derivation of the stability derivatives.
These derivatives are derived in the stability axis system as
defined by Blakelock (Ref. 2).

Reference 13 contains wind tunnel data for the Jindivik in various configurations, including one when fitted with the Air Cushion Recovery System (ACRS). The ACRS is the air cushion trunk with which the drone lands, but it also has an Air Cushion Takeoff System (ACTS) trunk with which it takes off. After takeoff, the ACTS is disengaged and drops to the ground. Both trunks are the same shape with the ACTS being about 21% larger in all dimensions. Since no wind tunnel data was available for the ACTS, the data for the ACRS was extrapolated by percentages and assumed to be fairly accurate for the ACTS. An example of the estimation technique is that the increase in the frontal area of the aircraft due to the replacement of the ACRS by the ACTS was 6%; therefore, the values of the coefficient of drag (C_D) were increased by 7%. Since the trunk does not generate lift, the coefficient of lift (C_L) was not affected, nor was the coefficient of side force (C_y); symmetry about the x-z axis meant that the coefficient of yawing moment (C_n) was not affected. The pitching moment coefficient (C_m) and rolling moment coefficient (C_ℓ) were affected by the percentage that the increased drag affected those moments. Thus, C_D , C_L , C_y , C_ℓ , C_m , and C_n can be empirically determined as functions of the angle of attack (α), the sideslip (β), and the elevator deflection (δ_e). In other words $\frac{\partial C_D}{\partial \alpha}$, $\frac{\partial C_D}{\partial \beta}$, $\frac{\partial C_D}{\partial \delta_e}$, $\frac{\partial C_L}{\partial \alpha}$, $\frac{\partial C_L}{\partial \delta_e}$, $\frac{\partial C_y}{\partial \beta}$, $\frac{\partial C_\ell}{\partial \beta}$, $\frac{\partial C_m}{\partial \alpha}$, $\frac{\partial C_m}{\partial \delta_e}$, and $\frac{\partial C_m}{\partial \beta}$ can be found from the wind tunnel data.

Non-dimensional derivatives were calculated because they provided a means of checking typical values and signs with

Roskam (Ref. 17) and Blakelock (Ref. 2). Before entering the derivatives into the EASY program, they were dimensionalized.

At low airspeeds the heave motion of the air cushion can create angles of attack beyond the stall limit, but at these speeds aerodynamic contributions to the aircraft dynamics are small.

Stability Derivative Derivation

C_L

From a curve of C_L vs. α of the wind tunnel data it can be shown that

$$C_L = C_{L_0} + \frac{\partial C_L}{\partial \alpha} \alpha \tag{22}$$

C_{L_0} and $C_{L_\alpha} \triangleq \frac{\partial C_L}{\partial \alpha}$ can be determined directly as the C_L intercept and slope of the curve.

C_D

From a drag polar of C_L vs. C_D it can be shown that

$$\dot{C}_D = C_{D_0} + K C_L^2 \tag{23}$$

where C_{D_0} and K are determined by a curve fit of wind tunnel data of C_D and C_L. Substituting for C_L

$$\begin{aligned} C_D &= C_{D_0} + K(C_{L_0} + C_{L_\alpha}\alpha)^2 \\ &= C_{D_0} + K(C_{L_0}^2 + 2C_{L_0}C_{L_\alpha}\alpha + C_{L_\alpha}^2 \alpha^2) \end{aligned} \tag{24}$$

differentiating
$$\begin{aligned} \frac{\partial C_D}{\partial \alpha} &= K(2C_{L_0}C_{L_\alpha} + 2C_{L_\alpha}^2 \alpha) \\ &= 2KC_{L_\alpha}(C_{L_0} + C_{L_\alpha}\alpha) \end{aligned} \tag{25}$$

so
$$C_{D_\alpha} \triangleq \frac{\partial C_D}{\partial \alpha} = 2KC_{L_\alpha}C_L \tag{26}$$

Roskam (Ref. 17, pgs 4.12, 1.18, 4.25) shows that for velocities below 300 ft/sec the variation of lift, pitch moment, and drag with velocity is zero. Thus,

$$\frac{\partial C_D}{\partial u} = 0 = \frac{\partial C_L}{\partial u} = \frac{\partial C_m}{\partial u} \tag{27}$$

The quantities

$$\frac{\partial C_D}{\partial \delta e} \;,\; \frac{\partial C_D}{\partial \delta_f} \;,\; \frac{\partial C_L}{\partial \delta e} \;,\; \frac{\partial C_L}{\partial \delta_f} \;,\; \frac{\partial C_m}{\partial \alpha} \;,\; \frac{\partial C_m}{\partial \delta e} \;,\; \frac{\partial C_m}{\partial \delta_f}$$

were all computer from curve-fits of the wind tunnel data.

$\underline{C_{L\alpha}}$

From Roskam (Ref. 17) it can be shown that the angle of

attack of the tail in downwash is

$$\alpha_t = \alpha - i - \epsilon \tag{28}$$

and for a particular angle of attack

$$\Delta \alpha_t = - \Delta \epsilon$$
$$= \frac{\partial \epsilon}{\partial \alpha} \Delta \alpha$$
$$= \frac{\partial \epsilon}{\partial \alpha} \dot{\alpha} \Delta t$$
$$= \frac{\partial \epsilon}{\partial \alpha} \dot{\alpha} \frac{l_t}{u} \tag{29}$$

now the change in lift coefficient on the tail due to downwash is

$$\Delta C_{L_t} = C_{L\alpha_t} \Delta \alpha_t$$
$$= C_{L\alpha_t} \dot{\alpha} \frac{l_t}{u} \frac{\partial \epsilon}{\partial \alpha} \tag{30}$$

The change in aircraft lift is

$$\Delta C_L = \Delta C_{L_t} \frac{S_t}{S} \tag{31}$$

$$\frac{\partial C_L}{\partial \dot{\alpha}} = C_{L\alpha_t} \frac{l_t}{u} \frac{\partial \epsilon}{\partial \alpha} \frac{S_t}{S} \tag{32}$$

thus $(C_{L\dot{z}})_{TAIL} \triangleq \frac{\partial C_L}{\partial \dot{\alpha}} \frac{2u}{c} = \frac{2}{c} C_{L\alpha_t} l_t \frac{S_t}{S} \frac{\partial \epsilon}{\partial \alpha}$ (33)

where $C_{L\alpha_t} = \dfrac{AR \cos \lambda \, C_{L\alpha_{2-D}}}{AR \sqrt{1 + \left(\dfrac{C_{L\alpha_{2-D}} \cos \lambda}{\pi AR}\right)^2} + \dfrac{C_{L\alpha_{2-D}} \cos \lambda}{\pi}}$ (34)

$$C_{L\alpha_{2-D}} = 5.73 \tag{35}$$

λ is sweep angle and AR is aspect ratio (Ref. 7)

The wing contribution to $C_{L_{\dot{\alpha}}}$ is considerable but can not be estimated (using Roskam, DATCOM, etc.). So a "typical" value from Roskam of $C_{L_{\dot{\alpha}}} \simeq 1.5 \, \text{rad}^{-1}$ was used; fortunately this derivative is of minor importance (Ref. 17, p. 4·114).

$C_{m_{\dot{\alpha}}}$

The contribution of the wing was neglected because it will be negligible with respect to the tail contribution. The correction to the pitching moment due to downwash on the tail is

$$(\Delta C_m)_{TAIL} = -\Delta C_{L_t} \frac{S_t}{S} \frac{\ell_t}{c}$$

$$= -C_{L_{\alpha_t}} \frac{\partial \epsilon}{\partial \alpha} \frac{2}{c} \frac{\ell_t^2}{u} \frac{S_t}{S} \tag{36}$$

and

$$\frac{\partial C_m}{\partial \dot{\alpha}} = -\frac{C_{L_{\alpha_t}}}{c} \frac{\partial \epsilon}{\partial \alpha} \frac{\ell_t^2}{u} \frac{S_t}{S} \tag{37}$$

and

$$C_{m_{\dot{\alpha}}} \triangleq \frac{2u}{c} \frac{\partial C_m}{\partial \dot{\alpha}} = -\frac{2C_{L_{\alpha_t}} \ell_t^2 S_t}{c^2 S} \frac{\partial \epsilon}{\partial \alpha} \tag{38}$$

C_{L_q}

q changes the angle of attack on the tail by $\dfrac{q \ell_t}{u}$ radians (for quasistatic conditions)

so

$$\Delta \alpha_t = \frac{q \ell_t}{u} \tag{39}$$

and

$$\Delta C_L = \frac{S_t}{S} \Delta C_{L_t} = \frac{S_t}{S} C_{L_{\alpha_t}} \frac{q \ell_t}{u} \tag{40}$$

differentiating

$$\left(\frac{\partial C_L}{\partial q}\right)_{TAIL} = C_{L_{\alpha_t}} \frac{S_t}{S} \frac{\ell_t}{u} \tag{41}$$

and the contribution of the wing body is negligible in comparison to the tail (Ref. 17, p. 153)

now

$$C_{L_q} \triangleq \frac{2u}{c} \frac{\partial C_L}{\partial q} = \frac{2C_{L_{\alpha_t}} S_t \ell_t}{c S} \tag{42}$$

12

C_{mq}

The moment on the tail is

$$m_t = -\ell_t L_t$$
$$= -\ell_t C_{L_t} \bar{q} S_t \qquad (43)$$

and the change in moment due to a change in angle of attack is

$$\Delta m_t = -\bar{q} \, \ell_t \, S_t \, \Delta C_{L_t}$$
$$= -\bar{q} \, \ell_t \, S_t \, C_{L_{\alpha t}} \Delta \alpha_t$$
$$= -\bar{q} \, \frac{\ell_t^2 S_t}{u} C_{L_{\alpha t}} \, \dot{q} \qquad (44)$$

and

$$\Delta C_{m_t} = -\dot{q} \, \frac{\ell_t^2 C_{L_{\alpha t}} S_t}{u C S} \qquad (45)$$

$$\left(\frac{\partial C_m}{\partial \dot{q}}\right)_{TAIL} = -\frac{\ell_t^2 C_{L_{\alpha t}} S_t}{u C S} \qquad (46)$$

since the wing contribution is negligible with respect to the tail (Ref. 17, p. 153)

$$C_{mq} \triangleq \frac{2u}{c}\left(\frac{\partial C_m}{\partial \dot{q}}\right)_{TAIL} = -\frac{2\ell_t^2 C_{L_{\alpha t}} S_t}{c^2 S} \qquad (47)$$

β Derivatives

Wind tunnel data gave C_y, C_ℓ, and C_m vs. β for values of $|\beta| \leq 7°$, but in any takeoff with crosswind the sideslip will normally exceed $7°$. The normal takeoff procedure will be to initially line the aircraft into the relative wind at the center-line and change the heading as the aircraft gains speed. This procedure should keep β within $\pm 30°$ and the present data can be curve fitted and extrapolated to this value. Consequently, expressions can be obtained for $C_{y\beta}$, $C_{\ell\beta}$, and $C_{m\beta}$ from the data. The $\dot{\beta}$ derivatives have been assumed to be zero (Ref. 17). For the β, ρ, and λ derivatives the effect of sidewash on the tail has been neglected.

p Derivatives

C_{np}

The change in C_n from the tail side force due to roll rate p is

$$(\Delta C_n)_{tail} = -\frac{\Delta C_{y_F} S_F \ell_F}{Sb}$$

$$= -\frac{C_{L\alpha_F} p \, \beta_F \, S_F \, \ell_F}{U S b} \tag{48}$$

$$\left(\frac{\partial C_n}{\partial p}\right)_{tail} = -\frac{C_{L\alpha_F} \, \beta_F \, S_F \, \ell_F}{U S b} \tag{49}$$

where β_F is the mean height of the fin, and the effect of sidewash
has been neglected

so
$$(C_{np})_{tail} \cong \frac{2U}{b}\left(\frac{\partial C_n}{\partial p}\right)_{tail} = -\frac{2 C_{L\alpha_F} \, \beta_F \, S_F \, \ell_F}{S b^2} \tag{50}$$

The wing contribution is in two parts due to lift and drag. For positive
p the angle of attack is increased on the right wing and decreased on
the left; thus inclining and changing the lift and drag vectors of each
wing section. The inclination angle is $\theta_p = \frac{py}{U}$ where y is the spanwise
coordinate of the section. The change in lift is

$$\Delta L_{left} = \bar{q} \, C_{L\alpha} \, \Delta\alpha \, c \, dy$$

$$= \bar{q} \, C_{L\alpha} \frac{py}{U} c \, dy \tag{51}$$

and
$$\Delta L_{right} = -\bar{q} \, C_{L\alpha} \frac{py}{U} c \, dy \tag{52}$$

where $c \, dy$ is the area of the wing section.

So the change in the yawing moment due to lift is

$$\Delta n_{left} = -y \, \Delta L_{left} \frac{py}{U} \tag{53}$$

14

and
$$\Delta \mathcal{N}_{right} = y \, \Delta L_{right} \frac{py}{u} \tag{54}$$

so
$$\Delta \mathcal{N}_{sections} = - \frac{2\bar{q}c\,dy}{u^2} \, y \, C_{L\alpha} \, p^2 y^3 \tag{55}$$

and the total yawing moment of the wing is

$$\Delta \mathcal{N}_{total} = \int_0^{\frac{b}{2}} \Delta \mathcal{N}_{sections} \, dy$$

$$= -2 \frac{\bar{q}c\,p^2}{u^2} C_{L\alpha} \int_0^{\frac{b}{2}} y^3 dy$$

$$= - \frac{\bar{q}\,c\,C_{L\alpha}\,p^2 b^4}{32\,u^2} \tag{56}$$

and
$$\frac{\partial \mathcal{N}}{\partial p} = - \frac{\bar{q}\,c\,p\,b^4\,C_{L\alpha}}{16\,u^2} \tag{57}$$

$$(C_{np})_{wing\ lift} \triangleq \frac{2u}{S\bar{q}b^2} \frac{\partial \mathcal{N}}{\partial p} = - \frac{C_{L\alpha}\,p\,b^2\,c}{8\,Su} \tag{58}$$

the change in drag is
$$\Delta D_{left} = -\bar{q}\,C_{D\alpha}\,\Delta\alpha\,c\,dy$$
$$= -\bar{q}\,C_{D\alpha}\frac{py}{u}\,c\,dy \tag{59}$$

and
$$\Delta D_{right} = \bar{q}\,C_{D\alpha}\frac{py}{u}\,c\,dy \tag{60}$$

the corresponding change in yawing moment is

$$\Delta \mathcal{N}_{left} = y\,\frac{\bar{q}\,c\,C_{D\alpha}}{u}\,py\,dy \tag{61}$$

and
$$\Delta \mathcal{N}_{right} = \bar{q}\,\frac{C_{D\alpha}\,p\,y^2}{u}\,c\,dy \tag{62}$$

so
$$\Delta \mathcal{N}_{sections} = 2\bar{q}\,\frac{C_{D\alpha}\,p\,y^2\,c\,dy}{u} \tag{63}$$

15

and
$$\Delta \eta_{total} = 2 \bar{q} \frac{c C_{D\alpha} P}{u} \int_0^{\frac{b}{2}} y^2 dy$$

$$= \frac{\bar{q} c C_{D\alpha} P b^3}{12 u} \tag{64}$$

now
$$\frac{\partial \eta}{\partial P} = \frac{\bar{q} c C_{D\alpha} b^3}{12 u} \tag{65}$$

and
$$(C_{mP})_{drag} \triangleq \frac{2u}{S\bar{q} b^2} \frac{\partial \eta}{\partial P} = \frac{C_{D\alpha} b c}{6 S} \tag{66}$$

summing all effects
$$C_{mP} = -\frac{2 C_{L\alpha_F} \partial_F \ell_F S_F}{S b^2} - \frac{C_{L\alpha} P b^2 \bar{q}}{8 u \bar{q}} + \frac{C_{D\alpha} b \bar{q}}{6 \bar{q}}$$

$$= -\frac{2 C_{L\alpha_F} \partial_F \ell_F S_F}{S b^2} - \frac{C_{L\alpha} P b}{8 u} + \frac{C_{D\alpha}}{6} \tag{67}$$

C_{yp}

C_{yp} is often negligible (Ref. 17, p. 170) and the tail is the major contributor. Let the mean change in angle of attack of the vertical stabilizer (fin) be

$$\Delta \alpha_F = -\frac{P \partial_F}{u} \tag{68}$$

where ∂_F is the mean height of the fin

now
$$\Delta C_{y_F} = C_{L\alpha_F} \Delta \alpha_F$$

$$= -C_{L\alpha_F} \frac{P \partial_F}{u} \tag{69}$$

so the change on the side force coefficient of the aircraft is (sidewash is neglected)

$$\Delta C_y = \frac{S_F}{S} \Delta C_{y_F} = -\frac{S_F}{S} \frac{P \partial_F}{u} C_{L\alpha_F} \tag{70}$$

so
$$\frac{\partial C_y}{\partial P} = -\frac{S_F}{S} \frac{\partial_F}{u} C_{L\alpha_F} \tag{71}$$

and
$$C_{yp} = \frac{2u}{b} \frac{\partial C_y}{\partial P} = -\frac{2 S_F \partial_F C_{L\alpha_F}}{S b} \tag{72}$$

16

$$\underline{C_{\ell_p}}$$

The wing is the only major contributor (Ref. 17, p. 170). Etkin (Ref. 9) shows that the rolling velocity, P , produces a change in the angle of attack of each wing section which is proportional to the span, i.e.,

$$\Delta \alpha = \frac{py}{u} \tag{73}$$

where y is the spanwise coordinate of the wing section. Then the lift distribution on the wing due to rolling is estimated to be

Etkin (Ref. 9) changes the triangular lift distribution to a sinusoidal distribution to account for the loss of lift at the wing tips due to spanwise flow around the wing tips. However, since the Jindivik has large tip tanks the lateral airflow will be minimized and the lift distribution will be closer to the triangular distribution shown.

The change in lift will be

$$\Delta L = 2 \bar{q} C_{L_\alpha} \Delta \alpha c \, dy$$

$$= 2 \bar{q} C_{L_\alpha} \frac{cpy}{u} \, dy \tag{74}$$

and the change in rolling moment due to this lift will be

$$\Delta \ell = -y \bar{q} C_{L_\alpha} \frac{cpy}{u} \, dy \tag{75}$$

thus
$$\mathcal{L} = -\bar{q}\, \frac{c\, C_{L_\alpha} p}{u} \int_o^{\frac{b}{2}} y^2 dy$$

$$= -\bar{q}\, \frac{c\, C_{L_\alpha} p\, b^3}{24\, u} \tag{76}$$

so
$$\frac{\partial \mathcal{L}}{\partial p} = -\bar{q}\, \frac{c\, C_{L_\alpha} b^3}{24\, u} \tag{77}$$

and
$$\frac{\partial C_L}{\partial p} \triangleq \frac{1}{\bar{q} S b}\, \frac{\partial \mathcal{L}}{\partial p} = -\frac{C_{L_\alpha} b^2 c}{S\, 24\, u} \tag{78}$$

so
$$C_{\ell_p} \triangleq \frac{2u}{b}\, \frac{\partial C_\ell}{\partial p} = -\frac{C_{L_\alpha} b c}{12 S} = -\frac{C_{L_\alpha}}{12} \tag{79}$$

r Derivatives

C_{yr}

The tail is the prime contributor (Ref. 17, p. 174). The change in fin angle of attack due to a yaw rate is

$$\Delta \alpha_F = \frac{r\, l_F}{u} \tag{80}$$

so the change in side force due to the tail is

$$\Delta C_y = C_{L_{\alpha_F}}\, \frac{S_F\, r\, l_F}{S\, u} \tag{81}$$

$$\frac{\partial C_y}{\partial r} = C_{L_{\alpha_F}}\, \frac{S_F\, l_F}{S\, u} \tag{82}$$

$$C_{yr} \triangleq \frac{2u}{b}\, \frac{\partial C_y}{\partial r} = \frac{2 C_{L_{\alpha_F}}\, S_F\, l_F}{S\, b} \tag{83}$$

$C_{\ell r}$

Contributions are from the wing and tail. The side force on the tail acts at $\jmath_F$, the mean height of the fin

and
$$\Delta F_y = \Delta C_y\, \bar{q}\, S$$
$$= \bar{q}\, S\, C_{L_{\alpha_F}}\, \frac{S_F\, r\, l_F}{S\, u} \tag{84}$$

18

now

$$\Delta \mathcal{L} = \Delta F_y \, \mathcal{J}_F$$

$$= \bar{q} S C_{L\alpha_F} \frac{S_F \, r \, l_F \, \mathcal{J}_F}{S \, u} \tag{85}$$

differentiating

$$\frac{d\mathcal{L}}{dr} = \bar{q} S \, C_{L\alpha_F} \frac{S_F \, l_F \, \mathcal{J}_F}{S \, u} \tag{86}$$

and

$$(C_{lr})_{tail} = \frac{2u}{b} \frac{1}{S\bar{q}b} \frac{d\mathcal{L}}{dr}$$

$$= \frac{2 C_{L\alpha_F} S_F \, l_F \, \mathcal{J}_F}{S b^2} \tag{87}$$

A positive r also increases lift on the left wing and decreases it on the right; the change in lift on each wing section is

$$\Delta L_{left\ section} = \Delta \bar{q} \, C_L c \, dy$$

$$= \frac{1}{2} \rho \, (\Delta u)^2 \, C_L c \, dy$$

$$= \frac{1}{2} \rho \, (ry)^2 \, C_L c \, dy \tag{88}$$

and

$$\Delta L_{right\ section} = - \Delta \bar{q} \, C_L c \, dy$$

$$= -\frac{1}{2} \rho \, (ry)^2 \, C_L c \, dy \tag{89}$$

now the change in rolling moment due to two sections at y is

$$\Delta \mathcal{L} = \rho r^2 y^3 \, C_L c \, dy \tag{90}$$

and the total rolling moment change for the wing is

$$\Delta \mathcal{L} = \rho r^2 \, C_L c \int_0^{b/2} y^3 dy$$

$$= \frac{\rho r^2 \, C_L c \, b^4}{64}$$

$$= \bar{q} \frac{r^2 C_L c \, b^4}{32 u^2} \tag{91}$$

19

now

$$\frac{\partial \mathcal{L}}{\partial r} = \frac{\bar{q} \, r \, C_i \, c \, b^4}{16 \, u^2} \tag{92}$$

$$\left(\frac{\partial C_\ell}{\partial r}\right)_{wing} \triangleq \frac{1}{S \bar{q} b} \frac{\partial \mathcal{L}}{\partial r} = \frac{r \, C_L \, b^2}{16 \, u^2} \tag{93}$$

and

$$\left(C_{\ell r}\right)_{wing} \triangleq \frac{2u}{b} \frac{\partial C_\ell}{\partial r} = \frac{r \, C_L \, b}{8 \, u} \tag{94}$$

summing the components

$$C_{\ell r} = \frac{2 C_{L\alpha_F} \, S_F \, \ell_F \, \mathcal{D}_F}{S \, b^2} + \frac{r \, C_L \, b}{8 \, u} \tag{95}$$

C_{nr}

The tail and wing contribute to C_{nr}. Knowing that the change in the fin angle of attack is

$$\Delta \alpha_F = \frac{-r \, \ell_F}{u} \tag{96}$$

and the moment arm of the tail is ℓ_F then

$$\left(\Delta \eta\right)_{tail} = -\frac{\ell_F \, C_{L\alpha_F} \, S_F \, r \, \ell_F \, \bar{q} \, S}{S \, u} \tag{97}$$

so

$$\left(\frac{\partial \eta}{\partial r}\right)_{tail} = -\bar{q} \, S \, C_{L\alpha_F} \frac{S_F \, \ell_F^2}{S \, u} \tag{98}$$

so

$$\left(C_{nr}\right)_{tail} \triangleq -\frac{2u}{b} \frac{1}{S \bar{q} b} \frac{\partial \eta}{\partial r}$$

$$= -2 C_{L\alpha_F} \frac{S_F \, \ell_F^2}{S \, b^2} \tag{99}$$

A positive λ increases the drag on the left wing and decreases drag on the right wing. The change in drag on each wing section is

$$\Delta D_{left\ section} = \Delta \bar{q}\, C_D\, c\, dy$$
$$= \frac{1}{2}\, \rho\, C_D\, (\Delta u)^2\, c\, dy$$
$$= \frac{1}{2}\, \rho\, C_D\, \lambda^2\, y^2\, c\, dy \qquad (100)$$

and
$$\Delta D_{right\ section} = -\frac{1}{2}\, \rho\, C_D\, \lambda^2\, y^2\, c\, dy \qquad (101)$$

so the change in yawing moment is

$$\Delta \eta = -\rho\, C_D\, \lambda^2\, c\, \int_0^{\frac{b}{2}} y^3\, dy$$
$$= -\frac{\rho\, C_D\, \lambda^2\, c\, b^4}{64} \qquad (102)$$

now
$$\frac{\partial \eta}{\partial \lambda} = -\frac{\rho\, C_D\, \lambda\, c\, b^4}{32} = -\frac{\bar{q}\, C_D\, \lambda\, c\, b^4}{16\, u^2} \qquad (103)$$

and
$$(C_{n\lambda})_{wing} = \frac{2u}{b}\, \frac{1}{S\bar{q}b}\, \frac{\partial \eta}{\partial \lambda} = -\frac{C_D\, \lambda\, b}{8u} \qquad (104)$$

summing the components

$$C_{n\lambda} = -\frac{2\, C_{L\alpha F}\, S_F\, \ell_F^2}{S\, b^2} - \frac{C_D\, \lambda\, b}{8u} \qquad (105)$$

Once all the derivatives had been determined or estimated, Ref. 15 was used to convert to dimentional body-axis derivatives. The derivatives were the written into the EASY program.

Chapter III

The Air Cushion Model

The air cushion model used in this analysis is a truncated version of an ACLS model that was designed by Foster-Miller Associates Inc. of Waltham, Massachusetts for the National Aeronautics and Space Administration (NASA) (Ref. 4).

The basic ACTS configuration is shown in Fig. 5. The model includes four primary subsystems: (1) the fan, (2) the feeding system, (3) the trunk, and (5) the cushion. Air from the fan flows through the ducts and plenum (feeding system) and enters the trunk. The trunk has several rows of orifices that exhaust both to the cushion and the atmosphere. Thus, the airflow from the trunk has two components, one entering the cushion and the other leading directly to the atmosphere. The cushion flow exhausts to the atmosphere through the clearance gap formed between the trunk and ground. In addition to the basic flows described above, two other flows have been included in the model. These are the plenum bleed flow and the direct cushion flow. Plenum bleeding causes some of the air to flow directly from plenum to atmosphere, and has been used in some designs to improve the dynamic characteristics of the air supply system. Direct flow from the plenum to the cushion can also improve dynamic response. A pressure relief valve is also included in the basic configuration. It allows additional flow to vent from the plenum whenever the pressure exceeds a preset level, and thus improves stability by reducing fan stall.

The support force acting on the aircraft is made up of two components. The first occurs due to the cushion pressure acting over the cushion area. The second, which comes about only during ground contact, is given by the

Fig. 5.   Basic ACTS Configuration

contact pressure acting over the trunk contact area. The support

force, in general, also gives rise to a moment, given by the pro-

duct of the force and its distance from the CG of the aircraft.

In plan, the cushion has an oval shape, made up of a rec-

tangular section with semicircular ends. The lengths a and b are

the horizontal and vertical spacing between the points of attachment

of the trunk to the aircraft body. The initial (undeformed) trunk

shape is defined by the above two parameters and the perimeter ℓ_p

and height H_y as shown. S_h is the (uniform) spacing between the

rows of peripherally distributed orifices. The number of the

orifices is selected independently by the number of orifice rows

N_r and the number of orifices per row N_h. The cushion volume consists

of two parts: an active (dynamically varying) region and a dead (static)

23

region. The active volume depends on the trunk shape and ground pro-
file. The dead volume, which is a design variable, includes recesses
in the cushion cavity as shown.

The forces transferred to the aircraft act through the cushion
and trunk. To help calculate these forces, the trunk and cushion are
divided into segments as shown in Fig. 6. Each straight section of the
cushion and trunk is divided into M rectangular segments, while each
curved end is divided into N pie-shaped segments. Thus, the total
number of segments is 2 (M + N). All cushion and trunk parameters
are calculated first for each segment and then summed to give their
total system values.

The dynamic analysis of the vehicle system is best derived with
the help of two orthogonal coordinate frames of reference: a coordi-
nate frame fixed in space (inertial frame), and a coordinate frame
fixed to the vehicle (vehicle frame) with origin at the aircraft CG.
The reason for two frames can be appreciated by recognizing that:

(a) Newton's law for translation motion requires that the
    CG acceleration be expressed relative to the inertial
    frame.

(b) The corresponding law for rotational motion, while valid
    in both inertial and vehicle frames, is applied more con-
    veniently in the vehicle frame, because rotational inertia
    about any vehicle axis is constant, while the rotational
    inertia about any inertial (fixed) axis varies with air-
    craft position.

Accordingly, the two frames of reference have been defined as
shown in Fig. 7. The vehicle frame with origin at the aircraft CG

24

Fig. 6. Division of Trunk Into Segments

has roll, yaw and pitch axes x, y and z, respectively, fixed to the
aircraft body as shown. The inertial frame has corresponding axes
X, Y and Z fixed in space. The two frames coincide only when the air-
craft has not undergone any rotation from equilibrium.

In the analysis, the actual runway profile underneath the ACTS
is approximated by segments that coincide in plan with those of the
trunk and are parallel to the cushion hard surface as shown in Fig. 7.
With this model, all pressure forces act parallel to the vehicle yaw
axis so that the segment torque components about the aircraft CG can
be easily computed by multiplying the segment force by the fore-and-
aft and/or lateral separation between the segment and the CG.

(a) Side View

(b) Front View

Fig. 7. Inertial and Vehicle Coordinate Frames

AFIT/GE/EE/77D-43

The analytical model of the ACTS consists of a set of equations which when solved determines the pressures, flows, forces, and motion of the system for various aircraft and runway parameters. The overall ACTS system is divided into two interrelated systems: the flow system and the force system. These systems are shown in Fig. 8 and Fig. 9. The flow system establishes the pressure-flow relationship for various subsystems of the ACTS. The force system establishes the corresponding force-motion relationships. The interdependence of the two systems comes about because the trunk deflection obtained from the force system changes the volumes and orifice areas that form part of the flow system. Similarly, the cushion and trunk pressures found from the flow system give rise to forces and moments that form inputs to the force system.

The Trunk Model

The major component of the ACTS model is the trunk model because it determines the trunk shape parameters (volume, and orifice and contact areas), contact pressure distribution and damping that form inputs to the ACLS flow and force systems.

Trunk Shape. In past work, two analytical models have been developed for the trunk shape: the Membrane Trunk Model (Ref. 8) and the Frozen Trunk Model (Ref. 6). The shortcoming of both these analyses was that they modeled the side and end segments of the trunk in the same way while test data now confirm that the shorter curved end segments (front and rear) behave very differently from the longer, straight side segments. Fig. 10 shows the trunk cross section measured at the center of the side and end segments as the load on the cushion is increased. The entire side segment tends to bow outward and avoid ground contact, while the end segment remains virtually fixed, except for a flattening

27

Fig. 8. ACTS Flow System

Fig. 9. ACTS Force System

in the region that actually touches the ground. This difference in behavior occurs because the front segment is much smaller than the side segment and is curved. When the cushion pressure increases due to an increase in the load, the radially outward force causes the oval trunk planform to become more circular, as shown in Fig. 11. This causes a hoop tension force, T, to act around the trunk periphery. In the side segments, this force acts substantially normal to the side excursion, δ_s, so that its component resisting the motion is negligible and the side segment can thus bow outwards relatively unrestrained. In the end segments the situation is different, since the curvature of the segment causes the hoop tension to have a much higher component opposing the motion so that outward motion of the trunk ends is much smaller.

(a) <u>Side Segment</u>

(b) <u>End Segment</u>

Fig. 10.   Measured Trunk Profile

Fig. 11. Outward Excursion of Trunk Segments

31

Since hoop tension has very little effect on side trunk motion, the side segments can be considered as simple, two-dimensional membranes, as done in the Membrane Trunk Model. On the other hand, the fact that hoop tension restrains ("freezes") the trunk ends suggests that these segments be modeled by the Frozen Trunk Model. Thus, the logical step in trunk model improvement is to combine the two existing models and form the Hybrid Trunk Model, in which the sides are represented by the Membrane Model and the ends by the Frozen Model.

The Hybrid Trunk Model is essentially a limiting case analysis of trunk deflection. In general, best results will be obtained at the middle of the respective segments, i.e., at the center of the side segments, where the trunk behaves very much like an ideal membrane, and at the center of the end segments, where the trunk shape is truly fixed. In the transition region (at and near where the segments meet), the trunk will exhibit properties of both the membrane and frozen trunk approximations.

Contact Pressure. In addition to trunk and cushion shape, the trunk model also determines the pressure distribution in the ground contact zone. The analysis for pressure distribution is complicated by the fact that two separate effects must be considered: direct trunk-ground contact caused by the trunk pressure forcing the trunk against the ground, and airflow through the trunk holes into the interstices that remain in the contact zone.

When two bodies in contact are acted upon by a force, F, the actual contact occurs at a number of discrete regions rather than over the whole area, due to the inherent roughness of the contacting surfaces as shown in Fig. 12. Because the number of contact

32

Trunk Pressure, P_t

Cushion
Pressure, P_c

Atmospheric
Pressure, P_a

(a) Contact Geometry

Local
Trunk-Ground
Contact Pressure

Pressure
due to
Outflow
from Trunk

Mean
Contact
Pressure

P_c

P_t

P_a

(b) Theoretical Pressure Profile

Trunk Pressure

Mean
Contact
Pressure

Measured
Pressure
Profile

P_c

P_a

(c) Observed Pressure Distribution

Fig. 12. Pressure Distribution in Trunk Contact Zone

regions is large for a "smooth" surface, it was convenient to define an average contact pressure, $P_{av} = F/A$, acting as though the bodies were touching uniformly over the entire area, A. In fact, P_{av} equals the trunk pressure, P_t. For purposes of trunk outflow calculation, the pressure profile in the non-contacting regions is approximated by a linearly decreasing relationship as shown in Fig. 12. The driving pressure for flow through any trunk hole is thus given by the difference between the trunk pressure and the gap press at that location. This pressure distribution model has been compared to experimental data and has been quite accurate (within 10%) (Ref. 4).

Trunk Damping. In dynamic operation, the trunk is deformed cyclically both in tension and flexure, and energy dissipation in the trunk material gives rise to a damping force which opposes the strain rate. Because the present trunk analysis does not solve for strain (and hence strain rate), a damping model that links trunk material properties directly to trunk damping forces cannot be developed. An alternate approach in which the damping characteristics are modeled by dimensional analysis (similarity) based on test data thus appears more appropriate. In keeping with the method of approach outlined earlier, the trunk is divided into segments (Fig. 13) and a series of dashpots, one for each segment, is included in the model such that the segment damping force is proportional to the vertical velocity of the trunk segment.

Each dashpot models the energy dissipation characteristic of the trunk segment. Although all parts of the trunk dissipate energy, the major contributions will come from those parts that undergo high stress reversals, since the strain rate is highest in these sections. Observations of a trunk in dynamic operation suggest that the high

34

FIG. 13. The Trunk Damping Model

stress reversal regions lie along the periphery of the trunk-ground

contact zone, because it is here that the rate of change of trunk

slope (and hence stress) is high and constantly changing with the

time as the contact area changes. As a first order approximation,

the damping model derived here assumes that all the energy dissipa-

tion in the trunk is concentrated along the trunk-ground contact

periphery so that the damping coefficient of each dashpot depends

on the perimeter of the ground contact zone. This means that when

a segment is not contacting the ground it has zero damping and when

it is contacting the ground it has a damping coefficient proportional

to the contact perimeter.

Model Synopsis

The Flow System

(a) The fan is characterized by a static pressure rise element for

   forward and back flow in series with an inertance (duct) and a

   capacitance (volume).

(b) The trunk and cushion volume are found from the Hybrid Trunk Model,

   which characterizes the side trunk segment as an ideal two-dimen-

   sional membrane and the end segment as a "frozen" trunk.

(c) The orifice areas between the trunk and cushion, trunk and atmos-

   phere and cushion and atmosphere are found from the trunk shape

   as predicted by the Hybrid Trunk Model, along with the cushion

   orientation and ground profile.

(d) The pressure within the cushion, trunk and plenum is considered to

   be uniform.

(e) The pressure in the trunk/ground contact zone is found from the

   triangular profile given by the Hybrid Trunk Model.

36

(f) The flow through the plenum, trunk and cushion is governed by
the unsteady state flow continuity equation in which the air is
assumed to behave like a perfect gas and follow a polytropic ex-
pansion relationship.

(g) The flow through all orifices is found from the incompressible
flow square-law orifice equation.

The Force System

(a) The mean contact pressure in the trunk/ground contact zone is
equal to the trunk pressure.

(b) The trunk contact area and location relative to the aircraft CG
is found from the trunk shape predicted by the Hybrid Trunk Model.

(c) The cushion area and location relative to the aircraft CG is found
from the Hybrid Trunk Model. In width, the cushion extends between
the lowest (ground tangent) points of the side trunk segments. In
length, it extends between the ground tangent points of the end trunk
segments, or, if in ground contact, between the inner edges of the
contact zone.

(d) The total forces and moments acting on the aircraft occur due to
the mean trunk contact pressure acting over the contact area, the
cushion pressure acting over the cushion area, aerodynamic drag
and trunk damping losses caused by aircraft heave motion, and
trunk-ground friction.

(e) The forces and moments are found by dividing the cushion (and trunk)
into segments, approximating the actual ground profile underneath
the cushion by a similar set of segments parallel to the cushion,
computing the cushion and contact pressure forces and moments for
each segment, and then summing them to determine the total force

and moment about the aircraft CG.

(f) The heave motion of the aircraft is found by applying Newton's law
in the vertical direction to the aircraft CG.

(g) Angular accelerations in pitch and roll are obtained by applying
the theorem of moment of momentum about the aircraft pitch and roll
axes.

(h) A coordinate transformation is carried out to express vehicle frame
velocities and accelerations in terms of Euler angles and their de-
rivatives.

(i) The moment of momentum equations, expressed in terms of Euler angles
are integrated to give the angular position of the aircraft as a
function of time.

Chapter IV

Controller Design

During the low speed portion of the takeoff roll (to approximately 50 knots), the controls available are a yaw thruster on the rear fuselage and vertical roll thrusters on each wing tip. The roll thrusters can be directed up or down. During the takeoff sequence, the most unstable mode of the aircraft is the roll mode. Therefore, it was decided to control this mode and observe the control that was applied to the pitch mode through the inertial cross-coupling. Also, during takeoff the yaw angle will be controlled by the yaw thruster on the rear of the fuselage. With roll and yaw controlled, Eqn (4), which is rewritten here, can be simplified.

$$I_{xx}\dot{P} - I_{xz}(\dot{R} + PQ) + (I_{zz} - I_{yy})RQ = \mathcal{L} \tag{106}$$

Controlling roll and yaw means that $\dot{R}$ will be small and PQ and RQ (products of small numbers) will be small. Q can be considered small because the takeoff starts with zero initial conditions on P, Q, and R. With the above simplification and assuming that any roll inputs from the ground profile are impulsive, then the roll moment generated by the roll thrusters can be written as

$$I_{xx}\ddot{\phi} = \mathcal{L}_{THRUSTERS}$$
$$= \ell w F_T \tag{107}$$

so

$$\ddot{\phi}(t) = C F_T(t) \tag{108}$$

where

$$C = \frac{\ell w}{I_{xx}} = 8.28 \times 10^{-3}$$

now let
$$X_1 = \phi \tag{109}$$

$$X_2 = \dot{\phi} \tag{110}$$

and
$$u(t) = F_T(t) \tag{111}$$

so Eqn (108) can be rewritten as

$$\dot{X}_2(t) = C\, u(t) \tag{112}$$

and
$$\dot{X}_1(t) = X_2(t) \qquad \text{from Eqn (110)} \tag{113}$$

so
$$\dot{\underline{x}}(t) = \underbrace{\begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix}}_{\underline{A}} \underline{x}(t) + \underbrace{\begin{bmatrix} 0 \\ C \end{bmatrix}}_{\underline{B}} u(t) \tag{114}$$

For a minimum time Performance Index and for $|u(t)| \leq U_{max}$ an optimal control for this system can be shown to be a bang-bang control (Ref. 14, pgs 245-248). In other words, the control is a maximum (either positive or negative) whenever it is applied. Since the eigenvalues for $\underline{A}$ are both zero, Theorems 5.4-1 and 5.4-3 of Kirk (Ref. 14) show that an optimal control exists, is unique and has at most one switching.

Therefore, the control for a specified initial state must be

$$u^*(t) = \begin{cases} +U_{max}, & t_0 \leq t < t^*, \text{ or} \\ -U_{max}, & t_0 \leq t < t^*, \text{ or} \\ +U_{max} \text{ for } t_0 \leq t < t_1 \text{ AND } -U_{max} \text{ for } t_1 \leq t < t^*, \text{or} \\ -U_{max} \text{ for } t_0 \leq t < t_1 \text{ AND } +U_{max} \text{ for } t_1 \leq t < t^*, \text{or} \\ 0 \quad \text{ for } \underline{x}(t) = 0 \end{cases}$$

$$\tag{115}$$

Integrating Eqns (112) and (113) with $U = \pm U_{max}$ gives

$$x_2(t) = C \int U(t) \, dt$$
$$= \pm C U_{max} t + CC_2 \tag{116}$$

where C_2 is the value of x_2 at $t = t_o$

and

$$x_1(t) = \int x_2(t) \, dt$$
$$= \int (\pm C U_{max} t + CC_2) \, dt$$

$$= \frac{\pm C U_{max}}{2} t^2 + CC_2 t + C_1 \tag{117}$$

where C_1 is the value of x_1 at $t = t_o$

solving for t in (116)

$$t = \frac{x_2(t) - CC_2}{\pm C U_{max}} \tag{118}$$

substituting t into (117)

$$x_1(t) = \frac{\pm C U_{max}}{2 C^2 U_{max}^2} \left(x_2^2(t) - 2CC_2 x_2(t) + C^2 C_2^2 \right) \tag{119}$$
$$+ \frac{CC_2 (x_2(t) - CC_2)}{\pm C U_{max}} + C_1$$

for $U = + U_{max}$

$$x_1(t) = \frac{1}{2C U_{max}} x_2^2(t) - \frac{C_2 x_2(t)}{U_{max}} + \frac{CC_2^2}{2U_{max}} + \frac{C_2 x_2(t)}{U_{max}} - \frac{CC_2^2}{U_{max}} + C_1$$

$$= \frac{1}{2C U_{max}} x_2^2(t) + C_3 \tag{120}$$

where

$$C_3 = C_1 - \frac{CC_2^2}{2U_{max}} \tag{121}$$

for $u = - U_{max}$

$$X_1(t) = \frac{-1}{2CU_{max}} X_2^2(t) + \frac{C_2 X_2(t)}{U_{max}} - \frac{CC_2^2}{2U_{max}} - \frac{C_2 X_2(t)}{U_{max}} + \frac{CC_2^2}{U_{max}} + C_1$$

$$= \frac{-1}{2CU_{max}} X_2^2(t) + C_4 \tag{122}$$

where
$$C_4 = C_1 + \frac{CC_2^2}{2U_{max}} \tag{123}$$

the switching curve is

$$X_1(t) = \frac{-1}{2CU_{max}} X_2(t) | X_2(t)| \tag{124}$$

Let
$$SX = X_1(t) + \frac{1}{2CU_{max}} X_2(t) | X_2(t)| \tag{125}$$

so
$$U^*(t) = -\begin{bmatrix} -U_{max} , & SX > 0 \\ U_{max} , & SX < 0 \\ -U_{max} , & SX = 0 , X_2(t) > 0 \\ U_{max} , & SX = 0 , X_2(t) < 0 \\ 0 , & \underline{X}(t) = 0 \end{bmatrix} \tag{126}$$

It can be noted that this controller design is almost completely independent of the aircraft type. In the low speed range where aerodynamic controls are not effective, this design will help stabilize the roll mode of any aircraft. The only relationship between the aircraft and controller is that the thruster force is a function of roll inertia and wing span. Thus, this design becomes very versatile

and applicable to stabilize the roll mode of any ACLS aircraft.

A somewhat similar analysis will be made for the controller of the yaw thruster. The criterion for directional control is to keep the aircraft on the runway centreline during takeoff; this can be accomplished by minimizing the lateral deviation, y, and rate of deviation from the centreline, ẏ. This deviation and rate will be minimized by yawing the aircraft in a direction to oppose the disturbance with the use of the yaw thruster.

Prior to the installation of the air cushion, the directional stability of the Jindivik was controlled by a batsman at the end of the runway. His job was to steer the dolly (Fig. 1) to keep the aircraft on the centreline. The same batsman will visually sense lateral deviation and deviation rate and control the yaw acceleration to indirectly control the lateral deviation and rate.

Assuming that the pitch and roll angles are kept small, then the lateral acceleration (to correct a lateral displacement) in the inertial frame of reference of the runway is a function of the thrust and yaw angle.

$$\ddot{y} \simeq \frac{THRUST \, SIN \, \Psi}{MASS} \tag{127}$$

and since Ψ will be small ($\leq 30°$) to keep the aircraft on the runway centreline, then

$$\ddot{y} \simeq \frac{THRUST}{MASS} \, \Psi \tag{128}$$

Equation 128 can be implemented as shown in Fig. 14. With these control loops the desired yaw angle to zero lateral displacement

43

can be determined. Referring to Fig. 14

$$\psi_d = -K_1 \mathring{y} - K_2 y \tag{129}$$

the inner loop open loop transfer function is

$$(GH)_1 = \frac{K K_1}{s} \tag{130}$$

and the equivalent closed loop transfer function is

$$\begin{aligned} G_1 &= \frac{GH}{1+GH} \\ &= \frac{KK_1}{s + KK_1} \end{aligned} \tag{131}$$

the outer loop open loop transfer function is therefore

$$\begin{aligned} (GH)_2 &= \frac{G_1 K_2}{s} \\ &= \frac{K K_1 K_2}{s(s + KK_1)} \end{aligned} \tag{132}$$

this gives a root locus as shown in Fig. 15. For a damping ratio of 0.7 the closed loop roots are located at $\left(-\frac{KK_1}{2}, -\frac{KK_1}{2}\right)$, which gives a closed loop transfer function of

$$\begin{aligned} G_2 &= \frac{K K_1 K_2}{\left(s + \frac{KK_1}{2} \pm j\frac{KK_1}{2}\right)} \\ &= \frac{K K_1 K_2}{s^2 + KK_1 s + \frac{K^2 K_1^2}{2}} \end{aligned} \tag{133}$$

but

$$\begin{aligned} G_2 &= \frac{(GH)_2}{1 + (GH)_2} \\ &= \frac{K K_1 K_2}{s^2 + KK_1 s + KK_1 K_2} \end{aligned} \tag{134}$$

44

Fig. 14.   Feedback Control Loops for Lateral Acceleration

Fig. 15   Root Locus for Fig. 14

45

therefore equating denominator coefficients gives

$$K K_1 K_2 = \frac{K^2 K_1^2}{2}$$

or

$$K_2 = \frac{K K_1}{2}$$

$$= 9 \cdot 1 \, K_1 \tag{135}$$

Since K_1 is arbitrary, a value of 0.3 was selected, so

$$K_1 = 0 \cdot 3 \tag{136}$$

and

$$K_2 = 2 \cdot 73 \tag{137}$$

so the desired yaw angle is

$$\Psi_d = -0 \cdot 3 \, \dot{y} - 2 \cdot 73 \, y \tag{138}$$

The yaw angle is associated with the yaw thruster force by

$$I_{33} \ddot{\Psi} = \eta = F_{yT} \, l_w$$

$$\ddot{\Psi} = C_5 F_{yT} \tag{139}$$

where

$$C_5 = 2 \cdot 73 \times 10^{-3} \tag{140}$$

in matrix form

$$\begin{bmatrix} \dot{\Psi} \\ \ddot{\Psi} \end{bmatrix} = \begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix} \begin{bmatrix} \Psi \\ \dot{\Psi} \end{bmatrix} + \begin{bmatrix} 0 \\ C \end{bmatrix} F_{yT} \tag{141}$$

This equation is the same as Eqn. 114 for the roll thruster, and similarly a bang-bang control exists for which the switching function

is

$$SXYT = \Psi + \frac{\dot{\Psi} \, |\dot{\Psi}|}{2C \, F_{YTMAX}} \tag{142}$$

and the optimal control law is

$$F_{yr}^{*} = \begin{cases} -F_{YTMAX} &, \; SXYT > 0 \\ F_{YTMAX} &, \; SXYT < 0 \\ -F_{YTMAX} &, \; SXYT = 0, \; \dot{\Psi} > 0 \\ F_{YTMAX} &, \; SXYT = 0, \; \dot{\Psi} < 0 \\ 0 &, \; \Psi = 0, \; \dot{\Psi} = 0 \end{cases} \tag{143}$$

The implementation of this control law would drive the yaw angle and yaw rate to zero in the minimum time, but the directional control problem requires that the yaw angle be equal to the desired angle, Ψ_d. This can be accomplished by shifting the switching curve by the amount Ψ_d.

$$SXYT = \Psi - \Psi_d + \frac{\dot{\Psi} \, |\dot{\Psi}|}{2C \, F_{YTMAX}} \tag{144}$$

This change in the switching curve means that the yaw rate and the quantity ($\Psi - \Psi_d$) will be driven to zero in the minimum time, or Ψ will equal Ψ_d.

Chapter V

The Computer Program and
Simulation Results

General

T.[.] EASY Dynamic Analysis Program to Aircraft Modelling (Ref. 5)
formed the major portion of the computer analysis and simulation and
the air cushion system was modelled by the Foster-Miller model, as
described in Chapter III. The computer program is listed in Appen-
dix B. In brief, the EASY program provided the means for an analysis
of the six degree of freedom rigid body dynamics of the Jindivik
drone and the Foster-Miller model estimated the ground forces and
moments transferred by the air cushion to the airframe. Additional
FORTRAN was used to reflect the Jindivik autopilot and the designed
roll, pitch and yaw controllers in the EASY program. Simulations
were performed to obtain time history comparisons of the uncontrolled
and controlled aircraft models with a crosswind driving function and
an initial pitch angle to simulate flying off of a 2 inch step.

The Computer Program

Figures 16, 17, and 18 show the computer block diagrams of
the aircraft dynamics, the longitudinal autopilot, and the lateral
autopilot, respectively. Understanding the symbology used in these
figures would require considerable referral to Reference 5, but a
general description of the schematics will be given here.

In Figure 16, SD performs the six degree of freedom rigid body
dynamics, AV calculates the aerodynamic variables, LO calculates the
longitudinal force and moment sum, and LD calculates the lateral force
and moment sum. The terms FX3S2, FZ3S2, TY3S2, TY3S2, TX3S2, and TZ3S2,
shown feeding into LO and LD, are the sums of the engine and external

48

Fig. 16. Block Diagram of Aircraft Dynamics

49

Fig. 17. Block Diagram of Longitudinal Autopilot

Fig. 18. Block Diagram of Lateral Autopilot

(i.e. air cushion system and controller) forces and moments.

The longitudinal and lateral autopilot functions shown in Figures 17 and 18 were developed from the elevator and aileron transfer functions given in Reference 3.. The maximum deflection of the control surfaces, the gearing ratios between control surfaces and servos, and the maximum slewing rates for the servos were also programmed into the model by FORTRAN.

Air Cushion Program

The air cushion system was programmed with ten subroutines to the EASY program and the flow chart of the subroutines is shown in Figure 19. The functions of the ten subroutines are as follows: FM is the main subroutine which calls and interacts with the remaining subroutines; it also determines the appropriate fan curve and contains the integration routine. HC, TK, SE, CO, PR, CL, S1, and SP form a set of subroutines which need the aircraft position, cushion and trunk pressures and ground profile as input parameters and they calculate various areas and volumes associated with those parameters. HC calculates the value of side trunk height for a given cushion to trunk pressure ratio. Subroutine TK takes that height and calculates trunk cross section parameters. From these parameters SE updates the trunk division parameters. Subroutine CO transforms position vectors for each trunk centre, from the vehicle frame to the ground frame, and then calculates the distance between each of the trunk segments and the ground, and it also calculates the ground coordinates above which each of the segments lie. Subroutine PR determines ground elevations (input by user) corresponding to the

Fig. 19. Air Cushion Subroutine Flow Chart

ground coordinates generated by CO, and subroutine CL determines the hard surface clearance for each segment using (a) the ground elevation value and (b) the distance of the trunk segment from the ground. Finally, subroutine SP calculates values of different areas and volumes for each segment and adds them together to give total areas and volumes.

In addition to these seven subroutines, FM also calls subroutine ST. ST determines the value of fan flow for a given value of fan pressure rise and also calculates the forces and torques for a given ACTS orientation. Subroutine ST also incorporates all the system differential equations so that the value of the state differentials can be updated each time it is called by the Runge-Kutta integration routine. The forces and torques calculated by ST are passed to the EASY program via FM.

Simulation Results

The results of the simulation to test the controller designs of Chapter IV are shown in Tables I and II. For initial conditions of $-1°$ in pitch, $0°$ in roll, and a constant 40 ft/sec crosswind, the uncontrolled model induces a roll angle and pitch angle that are lightly damped in comparison to the controlled model. Also, the restoring yaw angle is less than the controlled yaw angle and the lateral deviation, y, is subsequently greater for the uncontrolled model. The 1.5 second simulation for the uncontrolled model required 15,000 seconds of computation time and consequently the simulation was not continued to the extent

Table I - Simulation Results Uncontrolled Model

TIME	PITCH	ROLL	YAW	ALTITUDE	LATERAL DEVIATION
0.0	-1.000	0.000	0.00	2.60	0.00
0.5	.305	.113	-.63	1.52	3.84
1.0	.451	.474	-1.94	1.02	8.78
1.5	.377	.142	-2.51	1.25	14.87

Table II - Simulation Results Controlled Model

TIME	PITCH	ROLL	YAW	ALTITUDE	LATERAL DEVIATION
0.0	-1.000	0.000	0.0	2.60	0.00
0.5	.273	.150	-.74	1.71	3.83
1.0	.282	.072	-2.05	1.25	8.77
1.5	.063	.023	-3.82	2.32	14.68
2.0	.038	.005	-5.99	2.31	21.23
2.5	.045		-8.52	2.27	27.87
3.0	.052		-11.37	2.23	34.12
3.5	.048		-14.46	2.32	39.56
4.0			-17.70	2.32	43.74
4.5			-21.10	2.32	46.22
5.0			-24.50		46.52
5.5			-27.80		44.15
6.0			-30.90		38.56
6.5			-33.40		29.21
7.0			-34.80		15.69

Chapter VI

Conclusions and Recommendations

The National Aeronautics and Space Administration (NASA)
has accepted the Foster-Miller program as a valid air cushion
model; however, in the course of the analysis of this thesis,
several problems arose which prevent this program from be-
coming an effective design tool. The primary problem is the
excessive computation time required for dynamic simulation
when it is incorporated with the EASY Dynamic Analysis Program.
The Fourth Order Runge-Kutta integration routine used in the
air cushion model requires a time increment of 0.001 seconds
for numerical stability. Since this integration routine is the
prime reason for the excessive computation time, it is rec-
ommended that the routine be changed or augmented to reduce
computation time.

The air cushion model assumes that the trunk is an
elliptical shape rather than the actual shape, in which the
aft end is 10% wider than the fore end. This discrepancy
impinges on trunk and cushion volumes and areas, pitching
and rolling moments, clearance and gap areas, etc. In other
words, it requires considerable evaluation and extensive
modification and verification of the program to change trunk
shapes. It is recommended that Foster-Miller Associates be
asked to modify their model to accommodate different trunk
shapes as future designs may require.

The air cushion model has no provision to orient the trunk orifices other than perpendicular to the trunk surface. In fact, the Jindivik trunk orifices are drilled inward at a 45° angle to produce more cushion pressure in the region of trunk contact. Some adjustment should be made to the model to allow this orifice orientation as a design parameter. Also, the model uses a single curve to describe the fan characteristics of outflow vs. drive pressure, but the actual characteristics dependent on more variables; hence, a fan "map" is required r replace the single curve and adequately describe the fan during all phases of its operation.

A weak part of the computer simulation is the evaluation of the Jindivik Stability Derivatives due to the fact that the static wind tunnel data was extrapolated from the Recovery Trunk Data and was suspect from the beginning of the analysis. Consequently, it is recommended that wind tunnel tests be conducted in a moving belt tunne ith the takeoff trunk and with measurement of the rate variables p, q, and r. Barring this option, the development of the derivatives should be reviewed and ammended with the use of more sophisticated data reduction techniques. Once the computer program, shown in Appendix B, is changed to encompass the previous recommendations, it can be used to de-- fine the following parameters:

a) Operational limits and directions of crosswinds.

b) A "ground roughness" criteria above which the aircraft becomes unstable.

c) A flap deflection schedule to provide minimum takeoff distance within pitch stability. The present two flap settings would provide a step input to pitch and hence should be changed.

d) All of the above for different vertical thruster sizes and locations.

This thesis has integrated the EASY Dynamic Analysis Program and a truncated version of the Foster-Miller air cushion model to simulate an air cushion vehicle during takeoff. During the process of that integration and simulation, some major deficiencies in the Foster-Miller model have been highlighted. This thesis has also developed and demonstrated a technique to control bang-bang thrusters on the wing tips and a bang-bang thrust deflector on the tail section. Complete verification of the controller design was not possible due to the large computer resources that would have been required, but the results do show the control trends that are expected. The application of wing tip and yaw thrusters to other air cushion aircraft should provide comparable results. Also, these thrusters could be used on Vertical or Short Takeoff and Landing (V/STOL) aircraft because these aircraft also have marginal stability and require control enhancement in the low speed range.

Bibliography

1. <u>Air Cushion Launch Skirt-Jindivik</u>. Blueprint 03481-5X2024E, B. F. Goodrich Aerospace and Defense Products, Akron, Ohio, June 1974.

2. Blakelock, J. H. <u>Automatic Control of Aircraft and Missles</u>. Wiley, 1965.

3. Boeing Aerospace Co. Contract Report F33615-77-C-3054, June 1977.

4. Bogani, A. B., et al. <u>Heave, Pitch, and Roll Analysis and Testing of Air Cushion Landing Systems</u>. NASI-12403, Langley Research Center, Hampton, Virginia, March 1977.

5. Burrough, J. D. and Warren, A. W. <u>Applications of the EASY Dynamic Analysis Program to Aircraft Modelling</u>. User's Manual BCS40120, Boeing Computer Services, Inc., Seattle, Washington, 1976.

6. Captain, K. M., et al. <u>Dynamic Heave-Pitch Analysis of Air Cushion Landing Systems</u>. NASA CR-2530, May 1975.

7. Diedrick, F. W. <u>A Plan-Form Parameter for Correlating Certain Aerodynamic Characteristics of Swept Wings</u>. NACA TN 2335, April 1951.

8. Digges, K. H. <u>Theory of an Air Cushion Landing System for Aircraft</u>. TR-71-50, Air Force Flight Dynamics Laboratory, Wright-Patterson Air Force Base, Ohio, June 1971.

9. Etkin, B. <u>Dynamics of Flight: Stability and Control</u>. Wiley, New York, 1959.

10. <u>Fan Transition Assembly-Jindivik</u>. USAF Blueprint 13690214-012, Flight Dynamics Laboratory, Wright-Patterson Air Force Base, Ohio.

11. Fitzgerald, Robert E. <u>Jindivik Yaw Control Thrusters</u>. Chandler-Evans Inc., West Hartford, Connecticut, August 1975.

12. <u>General Arrangement of ACRS and ACTS-Jindivik Ground Tests</u>. USAF Blueprint 13690214-001, Flight Dynamics Laboratory, Wright-Patterson Air Force Base, Ohio.

13. Government Aircraft Factories (Australia), <u>GAF Project Report Jindivik No. B3B1/77</u> (Wind Tunnel Data), September 1976.

14. Kirk, Donald E. <u>Optimal Control Theory-An Introduction</u>. Prentice-Hall Inc., New Jersey, 1970.

15. McRuer, Askenas, and Graham, <u>Aircraft Dynamics and Automatic Control</u>. Prentice-Hall Inc., New Jersey, 1973.

16. <u>Preliminary Remotely Piloted Vehicle Air Cushion Landing System Static and Ground Tests on the Jindivik Drone.</u> TR-77-52 (Unpublished), Flight Dynamics Laboratory, Wright-Patterson Air Force Base, Ohio.

17. Roskam, J. <u>Flight Dynamics of Rigid and Elastic Airplanes</u>. Roskam Aviation and Engineering Corporation, Lawrence, Kansas, 1975.

18. <u>USAF Stability and Control Datcom</u>. Flight Control Division, Air Force Flight Dynamics Laboratory, Wright-Patterson Air Force Base, Ohio, January 1975.

Appendix A

Graphs of Aerodynamic Coefficients

FIG. A-1 LIFT COEFFICIENT VERSUS ANGLE OF ATTACK

FIG. A-2   PITCHING MOMENT COE EN
           VERSUS ANGLE OF ATTACK

FIG. A-3   DRAG COEFFICIENT VERSUS ANGLE OF ATTACK

FIG. A-4 SIDE FORCE COEFFICIENT VERSUS
SIDESLIP ANGLE

FIG. A-5   ROLL MOMENT COEFFICIENT VERSUS
SIDESLIP ANGLE

FIG. A-6   ROLL MOMENT COEFFICIENT VERSUS
SIDESLIP ANGLE

FIG. A-7   ROLL MOMENT COEFFICIENT VERSUS
          SIDESLIP ANGLE

FIG. A-8   ROLL MOMENT COEFFICSENT VERSUS
SIDESLIP ANGLE

FIG. A-9 YAW MOMENT COEFFICIENT VERSUS
SIDESLIP ANGLE

FIG. A-10 YAW MOMENT COEFFICIENT VERSUS
SIDESLIP ANGLE

FIG. A-11 YAW MOMENT COEFFICIENT VERSUS
SIDESLIP ANGLE

FIG. A-12 YAW MOMENT COEFFICIENT VERSUS
SIDESLIP ANGLE

Appendix B

Computer Program Listing

```
MODEL DESCRIPTION JINDIVIK ACTS (CONTROLLED)
ADD STATES=PQLFM,PTKFM,PCHFM
ADD PARAMETERS=A,E,L,LS,LX,MSS,    O,CC,FF,GG,      VCO,AH,        HYI,SH,
               CKK,PAT,GEC.                         TEM,
        JOV,                              CAF,CFX,CGP,CPA,CTC,PHA,
     CF2,CPC,COT,CTA,DPC,HDC          AAT,    AIF,              APC,APA,
     APT
ADD PARAMETERS=UMAX,UYTMAX
ADD VARIABLES=LCELS,RPM,Q1 TK,P2 TK,  SKTFM,              NDELS,BE SE,
    DXSE,L9,L9S,LJA,LP,LPS,LP,L9S,MAP, D2IS1,A1 S1,A2 S1,SI S1,OI S1,
    DXIS1,BEIS1,L1IS1,L2IS1,PIIS1,P2IS1,SNIS1,PHEDOT,THEDOT,   VTKS2,
    VCHS2,ACHS2,FY ST,TZ ST,TX ST,MWDS,               HY FM,HQ,HO,PFNFM,
    QFNFM,QFXFM,MO2,MOS,NPS,CSSFM,PRTFM,VCSFM,RHOFM,DVKFM,VPLFM,OVPFM,
    NP,NR,OVCFM,                    ATAS2,ATCS2,ACNS2,AACS2,ACCS2,   NPS,
    NDELS,NB,NRS,OPTFM,QTCFM,QTAFM,ATKCH,ATKAT,ATKCHC,ATKATC,OCHAT
    ,L1 TK,L2 TK,PH1TK,PH2TK
LOCATION=65,AV,INPUTS=50
FORTRAN STATEMENTS
C    ALL ANGLES IN DEGREES
     VS AV=100.  $FLAP=1. SOS=OS AV $ELE=ELELO $ALT=ALTSO $BE=BE AV
     RO=RO AV SPO=PO AV $VT=VT AV $QO=QO AV $AL=AL AV
     RADIAN=.0174532
     VH AV=40.*COS(YAWSO*RADIAN)
     BR=BE*RADIAN SAR=AL*RADIAN
C    CALCULATION OF COEFFICIENTS
     CLAFR=1.41 $ZFIN=3. $PUD=1. $C=4. SS=76. SRHO=23.77E-4 $9=19.
     STAIL=13. $XTAIL=10. $CLATR=3.05 $SFIN=7.2 $XFIN=10. SCLADR=1.5
     CLQR=(2.*CLATR*STAIL*XTAIL)/(C*S)
     CMQR=-2.*(XTAIL**2)*CLATR*STAIL/((C**2)*S)
     CYPR=2.*CLAFR*SFIN*XFIN/(S*9)
     CYPP=-2.*SFIN*CLAFR*ZFIN/(S*9)
C    INITIALIZE CONSTANTS
     CLO=.13 $SLOPE=.352 SCLALD=.0857 STL=.156 SCLALR=4.91
     GDEFF=.1-.395*ALT  SCLAIL=-.193*(1.-4.84E-9*VT**2)/57.3.
     IF(ALT.GT.30.)GDEFF=0.
  12 CL=(CLO+CLALD*AL+GDEFF)*COS(BR)
     CDI=.073+TL*CL**2+(1.6E-4*(ELE+10.)**2)
     CCALR=2.*TL*CLALR*CL
     CMADR=-2.*CLATR*(XTAIL**2)*STAIL*SLOPE/((C**2)*S)
     CNRR=-2.*CLAFR*SFIN*(XFIN**2)/(S*(9**2))-CC*RO*9/(8.*VT)
     CNPP=-2.*CLAFR*ZFIN*SFIN*XFIN/(S*9**2)-CLALR*PO*C/(8.*VT)+CDALR/6.
     CLPR=-CLALR/12.
     CLRR=2.*CLAFR*SFIN*XFIN*ZFIN/(S*9**2)+RO*CL*9/(8.*VT)
     CLDAR=34.73*CLALR*C/(S*9)
     CLELR=(6.49E-6*ELE**2-2.E-5*ELE+4.73E+3)*57.3
     CM=(-1.47E-4*AL**3+2.09E-3*AL**2-1.1E-2*AL+.057)*COS(BR)
     CMELR=(-19.2E-6*ELE**2+5.22E-5*ELE-1.2E-2)*57.3
     IF(ABS(BE).LT.60.) GO TO 210
     CYAW=SIN(BR)*5.6E-2
 210 IF(ABS(BE).LE.30.) GO TO 200
     CPOLL=-SIN(BR)*.2858
     CYT=SIN(BR)*3.1278
 200 IF(AL.LT.1.)GO TO 170
     IF((AL.GE.1.).AND.(AL.LT.3.))GO TO 180
     IF((AL.GE.1.).AND.(AL.LT.5.))GO TO 190
     IF(AL.GE.5.)GO TO 195
C    ANGLE OF ATTACK IS LESS THAN 1.0
 170 CD=CD1+(2.75E-6*ABS(BE)**3+2.29E-4*ABS(BE)**2-6.37E-4*ABS(BE))*COS
    X(BR)
     IF(ABS(BE).GE.60.) GO TO 2000
     IF(BE.LT.-7.) GO TO 30
     IF(BE.GE.7.) GO TO 40
     CYAW=-5.6E-6*BE**5+1.26E-7*BE**4+1.06E-5*BE**3+1.98E-6*BE**2-2.1E-
    X4*BE-7.03E-4
```

75

```
      CY=-4.39E-5*9E**3+1.68E-5*9E**2-1.33E-2*8E+2.56E-3
      CROLL=-1.14E-3*9E-2.35SE-3
      GO TO 2000
  30  CYAW=-.42E-4*9E+1.54E-3
      IF(ABS(9E).GT.30.) GO TO 2000
      CY=-4.39E-5*9E**3+1.68E-5*9E**2-1.33F-2*8E+2.56E-3
      CROLL=1.14E+3*9E+2.35SE-3
      GO TO 2000
  40  CYAW=4.42E-4*8E-.0025
      IF(ABS(9E).GT.30.) GO TO 2000
      CY=-4.39E-5*9E**3+1.68E-5*9E**2-1.33E-2*8E+2.56E-3
      CROLL=-1.14E-3*9E-2.355E-3
      GO TO 2000
C   ANGLE OF ATTACK IS LESS THAN 3.0
 180  CD=CC1+(-5.14E-6*A9S(9E)**3+3.03E-4*ABS(8E)**2-2.37E-4*ABS(8E)) *C
     XOS(BR)
      IF(ABS(9E).GE.60.) GO TO 2000
      IF(9E.LT.-7.) GO TO 50
      IF(9E.GE.7.) GO TO 60
      CYAW=-7.0E-9*9E**5-1.07E-6*9E**4+1.85E-5*9E**3+7.42E-5*9E**2-1.13E
     X-3*8E-1.34E-3
      CY=3.03E-7*9E**3+2.14E-6*9E**4-9.83E-5*9E**3-1.64E-4*9E**2-7.21E-
     X3*8E+8.16E-3
      CROLL=-1.53E-3*8E-1.26E-3
      GO TO 2000
  50  CYAW=-.3E-4*9E+5.67E-3
      IF(ABS(9E).GT.30.) GO TO 2000
      CY=3.03E-7*9E**3+2.14E-6*9E**4-9.83E-5*9E**3-1.64E-4*9E**2-7.21E-
     X3*8E+8.16E-3
      CROLL=-1.53E-3*9E-1.26E-3
      GO TO 2000
  60  CYAW=4.3E-4*9E-5.89E-3
      IF(ABS(9E).GT.30.) GO TO 2000
      CY=3.03E-7*9E**3+2.14E-6*9E**4-9.83E-5*9E**3-1.64E-4*9E**2-7.21E-
     X3*9E+8.16E-3
      CROLL=-1.53E-3*8E-1.26E-3
      GO TO 2000
C   ANGLE OF ATTACK IS LESS THAN 5.0
 190  CD=CD1+(-4.12E-5*ABS(8E)**3+2.5E-4*ABS(8E)**2-2.34E-4*ABS(8E))*COS
     X(BR)
      IF(ABS(8E).GE.60.) GO TO 2000
      IF(9E.LT.-7.) GO TO 70
      IF(8E.GE.7.) GO TO 80
      CYAW=-4.14E-7*8E**5-7.47E-7*8E**4+4.36E-5*8E**3+6.54E-5*9E**2-1.47
     XE-3*9E-1.83E-3
      CY=2.93E-6*9E**3+3.72E-7*9E**4-2.83E-4*8E**3-1.9E-5*8E**2 -4.06E-3
     X*8E+1.36E-2
      CROLL=-1.977E-3*9E-1.555E-3
      GO TO 2000
  70  CYAW=4.3E-4*9E+4.82E-3
      IF(ABS(9E).GT.30.) GO TO 2000
      CY=2.93E-6*9E**5+3.72E-7*8E**4-2.83E-4*9E**3-1.9E-5*8E**2 -4.06E-3
     X*9E+1.36E-2
      CROLL=-1.977E-3*9E-1.555E-3
      GO TO 2000
  80  CYAW=4.5E-4*9E-6.05E-3
      IF(ABS(9E).GT.30.) GO TO 2000
      CY=2.93E-6*9E**5+3.72E-7*9E**4-2.83E-4*9E**3-1.9E-5*9E**2 -4.06E-3
     X*8E+1.36E-2
      CROLL=-1.977E-3*9E-1.555E-3
      GO TO 2000
C   ANGLE OF ATTACK IS GREATER THAN 5.
 195  CD=CD1+(2.15E-5*ABS(9E)**3+1.61E-4*ABS(9E)**2-1.24E-3*ABS(8E))*COS
     X(PR)
      IF(ABS(9E).GE.60.) GO TO 2000
      IF(9E.LT.-7.) GO TO 90
```

76

```
      IF(BE.GE.7.) GO TO 100
      CYAW=1.28E-5*BE**3+1.23E-5*BE**2-8.21E-4*BE-5.33E-4
      CY=1.76E-6*BE**5-1 .91E-7*BE**4-1.8E-4*BE**3+2.72E-5*BE**2-5.82E-3
     X*BE+1.04E-2
      CROLL=-2.302E-3*BE-1.445E-3
      GO TO 2000
   90 CYAW=-.24E-4*BE+.0045
      IF(ABS(BE).GT.30.) GO TO 2000
      CY=1.76E-6*BE**5-1 .91E-7*BE**4-1.8E-4*BE**3+2.72E-5*BE**2-5.82E-3
     X*BE+1.04E-2
      CROLL=-2.302E-3*BE-1.445E-3
      GO TO 2000
  100 CYAW=4.24E-4*BE-4.3E-3
      IF(ABS(BE).GT.30.) GO TO 2000
      CY=1.76E-6*BE**5-1 .91E-7*BE**4-1.8E-4*BE**3+2.72E-5*BE**2-5.82E-3
     X*BE+1.04E-2
      CROLL=-2.302E-3*BE-1.445E-3
 2000 CONTINUE
C     DERIVATION OF DIMENTIONAL DERIVATIVES (STABILITY AXIS)
      ZWDS=-RHO*S*C/4.*CLADR
      ZOS=-OS/VT*C/2.*CLQR
      ZDELS=-OS*CLELR
      MWDS=RHO*S*C**2*CMADR/4.
      MOS=OS/VT*C**2*CMDR/2.
      MDELS=OS*CMELR*10.
      YDR=OS* CY
      NOR=OS*B*CYAW
      LOR=OS*B*CROLL
      YRS=RHO*S*3/4.*CYRR
      YPS=RHO*S*3/4.*CYPR
      NPS=OS/VT*3**2/4.*CNRR
      NPS=OS/VT*3**2/4.*CNPR
      LPS=OS/VT*3**2*CLRR/2.
      LPS=OS/VT*3**2*CLPR/2.
      LOELS=OS*B*CLAIL
      XOS=0.  SXWDS=0.  SMDELS=0.
C     DERIVATION OF DIMENTIONAL DERIVATIVES (BODY AXIS FROM STABILITY AXIS)
      XO=CL*OS*SIN(AR)-CD*OS*COS(AR)
      ZO=-CL*OS*COS(AR)-CD*OS*SIN(AR)
      MO=CM*CS*C
      XWD=(XWDS*COS(AR)**2-ZWDS*SIN(AR)*COS(AR))*COS(BR)
      ZAD=(ZWDS*COS(AR)**2+XWDS*SIN(AR)*COS(AR))*COS(BR)
      MAD=MWDS*COS(AR)*COS(BR)
      YP=YPS*COS(AR)-YRS*SIN(AR)
      YR=YPS*COS(AR)+YPS*SIN(AR)
      XDE=-ZDELS*SIN(AR)*COS(BR)
      XC=(XOS*COS(AR)-ZOS*SIN(AR))*COS(BR)
      ZO=(ZOS*COS(AR)+XOS*SIN(AR))*COS(BR)
      ZDE=ZDELS*COS(AR)*COS(BR)
      LP=(LPS*COS(AR)**2-(LPS+NPS)*SIN(AR)*COS(AR)+NRS*SIN(AR)**2)*COS(B
     XR)
      LDA=(LOELS*COS(AR)-NDELS*SIN(AR))*COS(BR)
      LR=(LRS*COS(AR)**2-(NPS-LPS)*SIN(AR)*COS(AR)-NPS*SIN(AR)**2)*COS(B
     XR)
      NP=(NPS*COS(AR)**2-(NPS-LPS)*SIN(AR)*COS(AR)-LRS*SIN(AR)**2)*COS(B
     XR)
      NR=(NRS*COS(AR)**2+(LPS+NPS)*SIN(AR)*COS(AR)+LPS*SIN(AR)**2)*COS(B
     XR)
             MO=MOS  SMDE=MDELS
   20 CONTINUE
      XO LO=XO  SXDELO=XDE  ZO LO=ZO  SZADLO=ZAD  SZO LO=ZO  SZDELO=ZDE
      MO LO=MO  SMADLO=MAD  SMO LO=MO  SMEELO=MDE  SYR LO=YR  SYO LO=YO
      YP LO=YP  SLO LO=LO  SLP LO=LP  SLR LO=LR  SLDALO=LDA  SNB LO=NB
      NP LO=NP  SNR LO=NP  SOS AV=OS  SELELO=ELE  SALTSO=ALT  SAL AV=AL
      BE AV=BE  SRO AV=RO  SRC AV=RO  SVT AV=VT  SOO AV=OO  INSP=32
      LORLO=LOR  SYDPLO=YDR  SNDPLO=NDR
```

```
LOCATION=142,EN
FORTRAN STATEMENTS
      RPM=330-.81+18.47*TH EN-1.84E-2*TH EN**2+9.23E-6*TH EN**3-1.67E-9*
     XTH EN**4
   10 CALL FM(HY FM,PCHFM,PTKFM,PPLFM,VTKS2,PFNFM,QFNFM,QFXFM,      IPPF
     1M,CSSFM,RPY,  VCSFM,RHOFM,DVKFM,VPLFM,DVPFM,      DVCFM,SKTFM,
     2 ALTSD,ROLSD,PITSD,PHEDOT,THEDOT,VCMS2,ACHS2,U  SD,W  SD,AL AV,P
     X SD,C  SD,R  SD,AM,MSS,PAF,    TEM,MYI,       OP1,R1 TK,R2 TK,L1
     XTK,L2 TK,PH1TK,           TX ST,FY ST,TZ ST,YAWSD,X2 IT 3,OPTFM,QTC
     XFM,QTAFM,ATKCH,ATKAT,ATKCHC,ATKATC,QCHAT,V  SD,PH2TK,L1IS1,L2IS1,I
     XSHAPE)
C**************** ROLL CONTROLLER ****************
      SX=ROLSD+(PO AV)*ABS(PO AV)/(2.*UMAX*8.18E-3)
      IF(SX.GT.0.)TXCON=-UMAX*20.
      IF(SX.LT.0.)TXCON= UMAX*20.
      IF((SX.EQ.0.).AND.(PO AV.GT.0.))TXCON=-UMAX*20.
      IF((SY.EQ.0.).AND.(PO AV.LT.0.))TXCON=UMAX*20.
      IF((ABS(RO.SD).EQ.0.0).AND.(ABS(PO AV).EQ.0.0)) TXCON=0.
C****************************************************
C**************** YAW CONTROLLER ****************
      UYTMAX=TH EN/23.
      SIEC=-0.30*YO SD-X2 IT 1
      SYTX=YAWSD-SIEC+R  SD*ABS(R  SD)*183.15/UYTMAX
      IF(SYTX.GT.0.)TZCON=-UYTMAX*10.
      IF(SYTX.LT.0.)TZCON= UYTMAX*10.
      IF((SYTX.EQ.0.).AND.(R  SD.GT.0 .))TZCON=-UYTMAX*10.
      IF((SYTX.EQ.0.).AND.(R  SD.LT.0.  ))TZCON=UYTMAX*10.
      IF((YAWSD.EQ. SIEC).AND.(R  SD.EQ.0.))TZCON=0.
C**************** PITCH CONTROLLER ****************
      SXPITCH=PITSD+(QO AV)*ABS(QO AV)/(2.*UMAX*6.52E-3)
      IF(SXPITCH.GT.0.)TYCON=-UMAX*12.
      IF(SXPITCH.LT.0.)TYCON= UMAX*12.
      IF((SXPITCH.EQ.0.).AND.(QO AV.GT.0.))TYCON=-UMAX*12.
      IF((SXPITCH.EQ.0.).AND.(QO AV.LT.0.))TYCON= UMAX*12.
      IF((ABS(PITSD).EQ.0.0).AND.(ABS(QO AV).EQ.0.0)) TYCON=0.
C****************************************************
      TX3S3=TXCON STY3S3=TYCON STZ3S3=TZCON SFZ2S3=-FY ST STX2S3=TX ST
      TY2S3=TZ ST
LOCATION=124,S3,INPUTS=EN
LOCATION=12,LD,INPUTS=AV,S3,MC 1(X=ELE)
LOCATION=44,LD,INPUTS=AV,LD,S3,MC 2(X=AIL)
LOCATION=37,SD,INPUTS=LD,LD
FORTRAN STATEMENTS
      ELEC=.29*(Q  SD-0.)+.333*(PITSD-0.)
      X1 TF=ELEC
LOCATION=149,TF
LOCATION=147,IT 7,INPUTS=TF
LOCATION=167,MC 1,INPUTS=TF,IT 7,IT 8
FORTRAN STATEMENTS
      IF(X4 MC 1.GE.10.) X4 MC 1=10.
      IF(X4 MC 1.LE.-15.) X4 MC 1=-15.
LOCATION=155,IT 3,INPUTS=MC 1
LOCATION=51,IT 3,INPUTS=SD(XO=X)
LOCATION=39 ,IT 1,INPUTS=SD(YO=X)
FORTRAN STATEMENTS
      AILC= .196*(P  SD-0.)+.42*(ROLSD+0.)+.2*R  SD
      X1 TF 2=AILC
LOCATION=248,TF 2
LOCATION=246,IT 3,INPUTS=TF 2
LOCATION=266,MC 2,INPUTS=TF 2,IT 9,IT10
FORTRAN STATEMENTS
      IF(X4 MC 2.GE.8. ) X4 MC 2=8.
      IF(X4 MC 2.LE.-8. ) X4 MC 2=-8.
LOCATION=254,IT1),INPUTS=MC 2
END OF MODEL
```

```
FORTRAN STATEMENTS
      SUBROUTINE FM(HY,PCH,PTK,PPL,VTK,PFN,QFN,QFX,     IPP,CSS,PPH,VCS,R
     1HO,DVK,VPL,DVP,DVC,SKT,YCG,THE,PHF,PHEDOT,THEDOT,VCHS2,ACHS2     ,U
     X,W,AL,F,O,R,AM,MSS,PAT,     TEM,HYI,          OP1,R1 TK,R2 TK,L1 TK,L
     X2 TK,PH1TK,     TX ST,FY ST,TZ ST,SIE,XCG,OPTFM,OTCFM,QTAFM,ATCS2,
     XATAS2,A?CS2,AACG2,QCMA?,V,PH2TK,L1IS1,L2IS1,ISHAPE)
      REAL L,LS,     MASS,     LK,L1IS1,L3TK,L2IS1,L2TK,MSS
      DIMENSION YC(13),SY(13),DELTA(32 ),SLSCO(32 ),ZCXSE(32 ),YCXSE(32 ),
     X,OELSE(32 ),ITYSE(32 ),XCISE(32 ),ZCISE(32 ),ISGSE(32 ),VTIS1(32 )
     X,ACIS1(32 ),YGHCL(32 ),ACFS2(32 ),ATIS2(32 ),PERS2(32 ),ATRS2(32 )
     X,XCHS2(32 ),XTKS2(32 ),ZCHS2(32 ),ZTKS2(32 ),DY ST(13),YG PR(32 ),
     XYO(13),Y1(13),Y2(13)
      DATA PI,RADIAN/3.141592653,0.01745327/
      CTIME=.0003     STINC=1.
C     AIR CUSHION LANDING SYSTEM PROGRAM
      MSS=77.3 SM=4 SN=4 ZCKK=1.4 SCAF=.5 SNSP=32 SVCD=0.     SCC=-1.17
      GG= 1.5  SFF=0. SPAT=21.5.3          SLS=4.125 SD=.417 SA=.695       SE
      ES.5248L=5.17 SHYI=1.0  SHX=3 SNH=195 SAH=3.4E-4 SSH=.0933 SLX=0.80
           CGP=.5 SGCC=.1          SCEX= 1.17 STEM=70.
      THEDOT=P S?HEDOT=Q SSKT=-W
      MASS=MSS          STEMPAT=TEM
           THETAE=THE SPHIE=PHE SOPHI=PHEDOT SDTHETA=THEDOT
                 NSTOP=NSP          SPPLM=PPL
C DATA ACQUISITION
      VPLM=.313 SVFAN=.468
      VPL=VPLM+VFAN
      DO 100 I=1,NSTOP
      DELTA(I)=0.0
100   CONTINUE
      RHO=1.241/(450.0+TEMPAT)
      HY=HYI
C  MINIMUM TRUNK HEIGHT IS PARKING SLATTER HEIGHT
      HY=AMAX1(HY,.78)
      CALL TK(ISHTK,PH2TK,P2 TK,R1 TK,PH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
      ISHAPE=ISHTK
      IF(ISHAPE.EQ.0) GO TO 139
      ICLFM=0
      CALL SE(ITYSE,BE SE,DY SE,ZCXSE,XCXSE,OELSE,XGISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,D2IS1,LS,H,N,D,ISGSE)
      CALL S1(D2IS1,A1 S1,A2 S1,SI S1,CI S1,DXIS1,BEIS1,L1IS1,L2IS1,R1IS
     11,P2IS1,SNIS1,PH2TK,P2 TK,DX SE,BE SE,HY,R1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,M,VTIS1,ACIS1,LS)
      FPLM=57.023-3.173E-2*RFM+5.33E-6*RPM**2-2.086E-10*RPM**3
      PFAN=PFLM
C INPUT PRESSURE AND OUTPUT FLOW
      IF((PPM.GE.11937.).AND.(PPM.LT.12075.)) GO TO 87
      IF((RPM.GE.12075.).AND.(RPM.LT.12213.)) GO TO 88
      IF((PPM.GE.12213.).AND.(PPM.LT.12351.)) GO TO 89
      IF((RPM.GE.12351.).AND.(RPM.LT.12489.)) GO TO 90
      IF((RPM.GE.12489.).AND.(RPM.LT.12627.)) GO TO 91
      IF((RPM.GE.12627.).AND.(RPM.LT.12765.)) GO TO 92
      IF((PPM.GE.12765.).AND.(PPM.LT.12903.)) GO TO 93
      IF((RPM.GE.12903.).AND.(RPM.LT.13041.)) GO TO 94
      IF((RPM.GE.13041.).AND.(RPM.LT.13179.)) GO TO 95
      IF((RPM.GE.13179.).AND.(RPM.LT.13317.)) GO TO 96
      IF((RPM.GE.13317.).AND.(RPM.LT.13455.)) GO TO 97
      IF((RPM.GE.13455.).AND.(RPM.LT.13593.)) GO TO 98
      IF((RPM.GE.13593.).AND.(RPM.LT.13731.)) GO TO 99
      IF((RPM.GE.13731.).AND.(RPM.LE.14000.)) GO TO 101
      IF( RPM.GT.14000.) GO TO 6
      IF( RPM.LT.11173.) GO TO 2
      IF((RPM.GE.11173.).AND.(RPM.LT.11385.)) GO TO 82
      IF((RPM.GE.11385.).AND.(RPM.LT.11523.)) GO TO 83
      IF((RPM.GE.11523.).AND.(RPM.LT.11661.)) GO TO 84
      IF((RPM.GE.11661.).AND.(RPM.LT.11799.)) GO TO 85
      IF((RPM.GE.11799.).AND.(RPM.LT.11937.)) GO TO 86
```

```
      2     PRINT 3
      3     FORMAT(*OFF LOWER END OF FAN_MAP*)
            GO TO 199
      4     PRINT 5
      5     FORMAT(* OFF UPPER END OF FAN MAP*)
            GO TO 199
C FAN CURVE FOR STATIC ITERATIONS
     82     QFAN=15.06      -.343    *PFAN+4.345-3   *PFAN**2-1.65E-5   *PFAN
            X**3       $GO TO 110
     83     QFAN=15.06      -.339    *PFAN+3.64E-3   *PFAN**2-1.39E-5   *PFAN
            X**3       $GO TO 110
     84     QFAN=11.33      -.154    *PFAN+1.74E-3   *PFAN**2-6.35-6    *PFAN
            X**3       $GO TO 110
     85     QFAN=10.82      -.129    *PFAN+1.29E-3   *PFAN**2-4.565-6   *PFAN
            X**3       $GO TO 110
     86     QFAN=9.73       -.077    *PFAN+7.15E-4   *PFAN**2-2.6E-6    *PFAN
            X**3       $GO TO 110
     87     QFAN=9.97       -.077    *PFAN+6.95E-4   *PFAN**2-2.45-6    *PFAN
            X**3       $GO TO 110
     88     QFAN=12.39      -.15     *PFAN+1.32E-3   *PFAN**2-3.96E-6   *PFAN
            X**3       $GO TO 110
     89     QFAN=18.38      -.333    *PFAN+2.87E-3   *PFAN**2-7.79E-6   *PFAN
            X**3       $GO TO 110
     90     QFAN=15.03      -.211    *PFAN+1.74E-3   *PFAN**2-4.67E-6   *PFAN
            X**3       $GO TO 110
     91     QFAN=12.73      -.13     *PFAN+1.03E-3   *PFAN**2-2.78E-6   *PFAN
            X**3       $GO TO 110
     92     QFAN=13.78      -.133    *PFAN+1.17E-3   *PFAN**2-3.01E-6   *PFAN
            X**3       $GO TO 110
     93     QFAN=13.74      -.142    *PFAN+1.05E-3   *PFAN**2-2.65-6    *PFAN
            X**3       $GO TO 110
     94     QFAN=12.05      -.086    *PFAN+5.925-4   *PFAN**2-1.55-6    *PFAN
            X**3       $GO TO 110
     95     QFAN=12.57      -.104    *PFAN+6.93E-4   *PFAN**2-1.63E-6   *PFAN
            X**3       $GO TO 110
     96     QFAN=11.59      -.062    *PFAN+3.78E-4   *PFAN**2-9.23-7    *PFAN
            X**3       $GO TO 110
     97     QFAN=12.6       -.079    *PFAN+4.79E-4   *PFAN**2-1.095-6   *PFAN
            X**3       $GO TO 110
     98     QFAN=18.29      -.206    *PFAN+1.29E-3   *PFAN**2-2.61E-6   *PFAN
            X**3       $GO TO 110
     99     QFAN=19.03      -.213    *PFAN+1.23E-3   *PFAN**2-2.53E-6   *PFAN
            X**3       $GO TO 110
    101     QFAN=32.07      -.432    *PFAN+2.98E-3   *PFAN**2-3.63E-6   *PFAN
            X**3
C           CHANGED Q FROM MASS FLOW TO VOLUME FLOW
    110     QFAN=QFAN/(RHO*32.2)
            QFANX=QFAN
            QFX=QFANX
            QFN=QFAN
            PFN=PFAN
            PPL=PPLN
C     CONVERT DEGREES TO RADIANS
            THETAE=THETAE*RADIAN
            PHIE=PHIE*RADIAN
            OTHETA=OTHETA*RADIAN
            OPHI=OPHI*RADIAN $SIE=SIE*RADIAN
            ICLN=0
            ICN=ICLN
C     OBTAIN INITIAL VALUE OF OCCHP AND INITIALIZE GEOMETRY
            PCHSS=(PCH+(PTK-PCH)*0.1)/PTK
            CSS=PCHSS
            CALL HC(Z   HC,CSS)
            HY=HYI*7  HC
C  MINIMUM TRUNK HEIGHT IS PARKING SLATTER HEIGHT
            HY=AMAX1(HY,,78)
```

80

```
      CALL TK(ISHTK,PH2TK,R2 TK,R1 TK,PH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
      ISHAPE=ISHTK
      IF(ISHAPE.EQ.0)GO TO 199
      ICLFM=1
      CALL SE(ITYSE,BE SE,DX SE,ZCXSE,XCXSE,DELSE,XCISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,D2IS1,LS,M,N,D,ISGSE)
      CALL CC(SL+CO,XCXSE,ZCXSE,YCG,XCG,SIE,PHE,THE,CC,FF,GG)
      CALL PR(YG PR)
      CALL CL(YGHCL,ICN,PHE,THE,SL4CO,YG PR)
      RHOFM=RHO
      CALL S1(D2IS1,A1 S1,A2 S1,SI S1,DI S1,DXIS1,BEIS1,L1IS1,L2IS1,R1IS
     11,R2IS1,SNIS1,PH2TK,R2 TK,DX SE,BE SE,HY,P1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,M,VTIS1,ACIS1,LS)
      CALL SF(VTKS2,VCHS2,ACHS2,PH2TK,F2 TK,D2IS1,BE SE,A1 S1,A2 S1,DX S
     1E,SI S1,      ITYSE,YGHCL,HY    ,(I S1,DXIS1,BEIS1,XCISE,ZCISE,L2 T
     2K,L1IS1,L2IS1,R1IS1,R2IS1,DELSE,SNIS1,XCXSE,D,LS,AH,NX,NH,HYI,LX,S
     3M,VCC,P1 TK,AGPS2,ATAS2,ATCS2,ACNS2,AACS2,ACCS2,ISGSE,VTIS1,ACIS1,
     XACRS2,ATIS2,ATRS2,PERS2,XCHS2,XTKS2,ZCHS2,ZTKS2,L,L1 TK)
      VCHSS=VCHS2
      VCS=VCHSS
      CALL HC(Z  HC,(PCH/PTK))
      HY=HYI*Z  HC
C MINIMUM TRUNK HEIGHT IS PARKING BLATTER HEIGHT
      HY=AMAX1(HY,.78)
      CALL TK(ISHTK,PH2TK,R2 TK,R1 TK,PH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
      ISHAPE=ISHTK
      IF(ISHAPE.EQ.0)GO TO 199
      CALL SE(ITYSE,BE SE,DX SE,ZCXSE,XCXSE,DELSE,XCISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,D2IS1,LS,M,N,D,ISGSE)
      CALL CO(SL,CO,XCXSE,ZCXSE,YCG,XCG,SIF,PHE,THE,CC,FF,GG)
      CALL PR(YG PR)
      CALL CL(YGHCL,ICN,PHE,THE,SL4CO,YG PR)
      CALL S1(D2IS1,A1 S1,A2 S1,SI S1,F1 S1,DXIS1,BEIS1,L1IS1,L2IS1,R1IS
     11,R2IS1,SNIS1,PH2TK,R2 TK,DX SE,BE SE,HY,P1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,M,VTIS1,ACIS1,LS)
      CALL SP(VTKS2,VCHS2,ACHS2,PH2TK,F2 TK,D2IS1,BE SE,A1 S1,A2 S1,DX S
     1E,SI S1,      ITYSE,YGHCL,HY    ,(I S1,DXIS1,BEIS1,XCISE,ZCISE,L2 T
     2K,L1IS1,L2IS1,R1IS1,R2IS1,DELSE,SNIS1,XCXSE,D,LS,AH,NX,NH,HYI,LX,S
     3M,VCC,R1 TK,AGPS2,ATAS2,ATCS2,ACNS2,AACS2,ACCS2,ISGSE,VTIS1,ACIS1,
     XACRS2,ATIS2,ATRS2,PERS2,XCHS2,XTKS2,ZCHS2,ZTKS2,L,L1 TK)
      OVCHP=(VCHS2-VCHSS)/((PCH/PTK)-PCHSS)
      OVP=OVCHP
C*****DYNAMIC SIMULATION********************************
      INUM=0
      OVTK=0.0
      OVK=DVTK
      OVCH=SKT*ACHS2
      OVC=OVCH
      CALL ST(FY ST,TZ ST,TY ST,DY ST,IPP,FPL,VPL,VTKS2,GFX,OVK,PTK,OVC,
     1YCG,CVP,PCH,VCHS2,SKT,PHE,PHEDOT,THE,THEDOT,CKK,PAT,GG,HYI,SEC,MSS
     2, RPM,             U,       SIF,RHO,AGPS2,ACHS2,ATAS2,ATCS2,ACNS
     32,AACS2,ACCS2,CAF,CFX,CGP,    ACFS2,ATIS2,ATRS2,PERS2,XCHS2,ZCHS2,
     3XTKS2,ZTKS2,ACIS1,YGHCL,OPTFM,OTCFM,CTAFM,OCHAT)
C********CALCULATE DVCH,DVCHP,DVTK AS CVC,CVP,OVK  ***************
      IF(INUM)200,1,200
   1  VCHS=VCHS2  3VTKS=VTKS2
 200  CALL TK(ISHTK,PH2TK,R2 TK,R1 TK,PH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
      ISHAPE=ISHTK
      ICLFM=1
      CALL SE(ITYSE,BE SE,DX SE,ZCXSE,XCXSE,DELSE,XCISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,D2IS1,LS,M,N,D,ISGSE)
      CALL CO(SL,CO,XCXSE,ZCXSE,YCG,XCG,SIF,PHE,THE,CC,FF,GG)
      CALL PR(YG PR)
      CALL CL(YGHCL,ICN,PHE,THE,SL4CO,YG PR)
      RHOFM=RHO
      CALL S1(D2IS1,A1 S1,A2 S1,SI S1,CI S1,DXIS1,BEIS1,L1IS1,L2IS1,R1IS
```

```
     11,R2IS1,SNIS1,PH2TK,P2 TK,DX SE,BE SE,HY,R1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,M,VTIS1,ACIS1,LS)
         CALL SP(VTKS2,VCHS2,ACHS2,PH2TK,F2 TK,D2IS1,BE SE,A1 S1,A2 S1,DX S
     1E,SI S1,       ITYSE,YGHCL,HY   ,DI S1,DXIS1,BEIS1,XCISE,ZCISE,L2 T
     2K,L1IS1,L2IS1,R1IS1,R2IS1,DELSE,SNIS1,XCXSE,D,LS,AH,NX,NM,HYI,LX,S
     3M,VCD,R1 TK,AGPS2,ATAS2,ATDS2,ACHS2,AACS2,ACCS2,ISGSE,VTIS1,ACIS1,
     XACRS2,ATIS2,ATRS2,PERS2,XCHS2,XTKS2,ZCHS2,ZTKS2,L,L1 TK)
         DVC=(VCHS2-VCHS)/.01
   C****** DVCHP CALCULATION *************************
         VCHSS=VCHS2 SPRAT=(PCH+(PTK-PCH)*.1)/PTK
         CALL HC(HX,PRAT)
         HY=HY*HYI
   C  MINIMUM TRUNK HEIGHT IS PARKING BLATTER HEIGHT
         HY=AMAX1(HY,.78)
         CALL TK(ISHTK,PH2TK,R2 TK,R1 TK,PH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
         ISHAPE=ISHTK
         IF(ISHAPE.EQ.0) GO TO 199
         CALL SE(ITYSE,BE SE,DX SE,ZCXSE,XCXSE,DELSE,XCISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,D2IS1,LS,M,N,D,ISGSE)
         CALL CC(SL,CO,XCXSE,ZCXSE,YCG,XCG,SIE,PHE,THE,CC,FF,GG)
         CALL PR(YG PR)
         CALL CL(YGHCL,ICN,PHE,THE,SL4CO,YG PR)
         RHOFM=RHO
         CALL S1(D2IS1,A1 S1,A2 S1,SI S1,CI S1,DXIS1,BEIS1,L1IS1,L2IS1,R1IS
     11,R2IS1,SNIS1,PH2TK,R2 TK,DX SE,BE SE,HY,R1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,M,VTIS1,ACIS1,LS)
         CALL SF(VTKS2,VCHS2,ACHS2,PH2TK,P2 TK,D2IS1,BE SE,A1 S1,A2 S1,DX S
     1E,SI S1,       ITYSE,YGHCL,HY   ,DI S1,DXIS1,BEIS1,XCISE,ZCISE,L2 T
     2K,L1IS1,L2IS1,R1IS1,R2IS1,DELSE,SNIS1,XCXSE,D,LS,AH,NX,NM,HYI,LX,S
     3M,VCD,R1 TK,AGPS2,ATAS2,ATDS2,ACHS2,AACS2,ACCS2,ISGSE,VTIS1,ACIS1,
     XACRS2,ATIS2,ATRS2,PERS2,XCHS2,XTKS2,ZCHS2,ZTKS2,L,L1 TK)
         DVP=(VCHSS-VCHS2)/((PCH/PTK)-PRAT)
         PRAT=AMAX1(0.0,AMIN1(1.0,(PCH/PTK)))
   C****** CALCULATE DVTK *************************
         CALL HC(HX,PRAT)
         HY=HY*HYI
   C  MINIMUM TRUNK HEIGHT IS PARKING BLATTER HEIGHT
         HY=AMAX1(HY,.75)
         CALL TK(ISHTK,PH2TK,R2 TK,R1 TK,PH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
         ISHAPE=ISHTK
         IF(ISHAPE.EQ.0) GO TO 199
         CALL SE(ITYSE,BE SE,DX SE,ZCXSE,XCXSE,DELSE,XCISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,D2IS1,LS,M,N,D,ISGSE)
         CALL CC(SL,CO,XCXSE,ZCXSE,YCG,XCG,SIE,PHE,THE,CC,FF,GG)
         CALL PR(YG PR)
         CALL CL(YGHCL,ICN,PHE,THE,SL4CO,YG PR)
         RHOFM=RHO
         CALL S1(D2IS1,A1 S1,A2 S1,SI S1,CI S1,DXIS1,BEIS1,L1IS1,L2IS1,R1IS
     11,R2IS1,SNIS1,PH2TK,R2 TK,DX SE,BE SE,HY,R1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,M,VTIS1,ACIS1,LS)
         CALL SP(VTKS2,VCHS2,ACHS2,PH2TK,F2 TK,D2IS1,BE SE,A1 S1,A2 S1,DX S
     1E,SI S1,       ITYSE,YGHCL,HY   ,DI S1,DXIS1,BEIS1,XCISE,ZCISE,L2 T
     2K,L1IS1,L2IS1,R1IS1,R2IS1,DELSE,SNIS1,XCXSE,D,LS,AH,NX,NM,HYI,LX,S
     3M,VCD,R1 TK,AGPS2,ATAS2,ATDS2,ACHS2,AACS2,ACCS2,ISGSE,VTIS1,ACIS1,
     XACRS2,ATIS2,ATRS2,PERS2,XCHS2,XTKS2,ZCHS2,ZTKS2,L,L1 TK)
         DVK=(VTKS2-VTKS)/.01
   C********* FOURTH ORDER RUNGE-KUTTA INTEGRATION ROUTINE ***************
         Y(1)=PPL  $Y(2)=PCH $Y(3)=PTK
         TIME=0.
   50    H=DTIME/2.
         DO 10 I=1,4
         SY(I)=Y(I)
         YO(I)=CY ST(I)
   10    Y(I)=Y(I)+H*DY ST(I)
         TIME=TIME+H
         Y(1)=PPL  $Y(2)=PCH $Y(3)=PTK
```

```
      CALL ST(FY ST,TZ ST,TX ST,DY ST,IPP,PPL,VPL,VTKS2,QFX,DVK,PTK,DVC,
     1YCG,DVP,PCH,VCHS2,SKT,PHE,PHEDOT,THE,THEDOT,CKK,PAT,GG,HYI,GEC,HSS
     2, RPM,              U,      SI',RHO,AGPS2,ACHS2,ATAS2,ATCS2,ACNS
     32,AACS2,ACSS2,CAF,CFX,CGP,     ACFS2,ATIS2,ATRS2,PERS2,XCHS2,ZCHS2,
     3XTKS2,ZTKS2,ACIS1,YGHCL,OPTFH,QTCFH,QTAFH,QCHAT)
      DO 20 I=1,4
      Y1(I)=DY ST(I)
   20 Y(I)=SY(I)+H*DY ST(I)
      Y(1)=PPL  SY(2)=PCH SY(3)=PTK
      CALL ST(FY ST,TZ ST,TX ST,DY ST,IPP,PPL,VPL,VTKS2,QFX,DVK,PTK,DVC,
     1YCG,DVP,PCH,VCHS2,SKT,PHE,PHEDOT,THE,THEDOT,CKK,PAT,GG,HYI,GEC,HSS
     2, RPM,              U,      SIE,PHO,AGPS2,ACHS2,ATAS2,ATCS2,ACNS
     32,AACS2,ACSS2,CAF,CFX,CGP,     ACFS2,ATIS2,ATRS2,PERS2,XCHS2,ZCHS2,
     3XTKS2,ZTKS2,ACIS1,YGHCL,OPTFH,QTCFH,QTAFH,QCHAT)
      DO 30 I=1,4
      Y2(I)=DY ST(I)
   30 Y(I)=SY(I)+DTIME*DY ST(I)
      Y(1)=PPL  SY(2)=PCH SY(3)=PTK
      CALL ST(FY ST,TZ ST,TX ST,DY ST,IPP,PPL,VPL,VTKS2,QFX,DVK,PTK,DVC,
     1YCG,DVP,PCH,VCHS2,SKT,PHE,PHEDOT,THE,THEDOT,CKK,PAT,GG,HYI,GEC,HSS
     2, RPM,              U,      SIE,RHO,AGPS2,ACHS2,ATAS2,ATCS2,ACNS
     32,AACS2,ACSS2,CAF,CFX,CGP,     ACFS2,ATIS2,ATRS2,PERS2,XCHS2,ZCHS2,
     3XTKS2,ZTKS2,ACIS1,YGHCL,OPTFH,QTCFH,QTAFH,QCHAT)
      TIME=TIME+H
      H=H/3.
      DO 40 I=1,4
      PRT1=2.0*(Y1(I)+Y2(I))
      PRT2=Y3(I)+DY ST(I)
      Y(I)=SY(I)+H*PRT1+H*PRT2
   40 CONTINUE
      PPL=Y(1)  PCH=Y(2) PTK=Y(3)
      CALL ST(FY ST,TZ ST,TX ST,DY ST,IPP,PPL,VPL,VTKS2,QFX,DVK,PTK,DVC,
     1YCG,DVP,PCH,VCHS2,SKT,PHE,PHEDOT,THE,THEDOT,CKK,PAT,GG,HYI,GEC,HSS
     2, RPM,              U,      SIE,PHO,AGPS2,ACHS2,ATAS2,ATCS2,ACNS
     32,AACS2,ACSS2,CAF,CFX,CGP,     ACFS2,ATIS2,ATRS2,PERS2,XCHS2,ZCHS2,
     3XTKS2,ZTKS2,ACIS1,YGHCL,OPTFH,QTCFH,QTAFH,QCHAT)
      IF((PPL-SY(1)).LT.1.) GO TO 60
      IF(TIME.LT.TINC) GO TO 50
   60 CONTINUE
      INUM=1
C********CALCULATE DVCH,DVCHP,DVTK AS DVC,DVP,DVK  ******************
      IF(INUM)201,11,201
   11 VCHS=VCHS2 DVTKS=VTKS2
  201 CALL TK(ISHTK,PH2TK,R2 TK,R1 TK,FH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
      ISHAPE=ISHTK
      ICLFM=1
      CALL SE(ITYSE,BE SE,DX S2,ZCXSE,XCXSE,DELSE,XCISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,D2IS1,LS.M,N,D,ISGSE)
      CALL CC(SL,CO,XCXSE,ZCXSE,YCG,XCG,SIE,PHE,THE,CC,FF,GG)
      CALL PR(YG PR)
      CALL CL(YGHCL,ISH,PHE,THE,SL,CO,YG PR)
      RHOFH=RHO
      CALL S1(D2IS1,A1 S1,A2 S1,SI S1,DI S1,DXIS1,BEIS1,L1IS1,L2IS1,R1IS
     11,R2IS1,SNIS1,PH2TK,P2 TK,DX SE,PE SE,HY,R1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,H,VTIS1,ICIS1,LS)
      CALL SF(VTKS2,VCHS2,ACHS2,PH2TK,F2 TK,D2IS1,BE SE,A1 S1,A2 S1,DX S
     1E,SI S1,    ITYSE,YGHCL,HY   ,LI S1,CXIS1,DEIS1,XCISE,ZCISE,L2 T
     2K,L1IS1,L2IS1,R1IS1,R2IS1,DELSE,SNIS1,YCXSE,D,LS,AH,NX,NH,HYI,LX,S
     3H,VCD,R1 TK,AGPS2,ATACD,ATCS2,ACNS2,AACS2,ACCS2,ISGSE,VTIS1,ACIS1,
     XACPS2,ATIS2,ATRS2,PERS2,XCHS2,XTKS2,ZCHS2,ZTKS2,L,L1 TK)
      DVC=(VCHS2-VCHS)/.01
C******* DVCHP CALCULATION ************************
      VCHSS=VCHS2 SPRAT=(PCH+(PTK-PCH)*.1)/PTK
      CALL HC(HX,PRAT)
      HY=HX*HYI
      CALL TK(ISHTK,PH2TK,R2 TK,R1 TK,FH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
```

```
      ISHAPE=ISHTK
      IF(ISHAPE.EO.0) GO TO 199
      CALL SE(ITYSE,BE SE,DX SE,ZCXSE,XCXSE,DELSE,XCISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,O2IS1,LS,M,N,O,ISGSE)
      CALL CO(SL,CO,XCXSE,ZCXSE,YSG,XCG,SIE,PHE,THE,CC,FF,GG)
      CALL PR(YG PR)
      CALL CL(YGHCL,ICN,PHE,THE,SL&CO,YG PR)
      RHOFM=RHO
      CALL S1(O2IS1,A1 S1,A2 S1,SI S1,CI S1,OXIS1,BEIS1,L1IS1,L2IS1,R1IS
     11,R2IS1,SNIS1,PH2TK,R2 TK,DX SE,FE SE,HY,R1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,M,VTIS1,ACIS1,LS)
      CALL SP(VTKS2,VCHS2,ACHS2,PH2TK,R2 TK,O2IS1,BE SE,A1 S1,A2 S1,DX S
     1E,SI S1,      ITYSE,YGHCL,HY   ,CI S1,OXIS1,BEIS1,XCISE,ZCISE,L2 T
     2K,L1IS1,L2IS1,R1IS1,R2IS1,DELSE,SNIS1,YCXSE,O,LS,AM,NX,NM,HYI,LX,S
     3M,VCO,R1 TK,AGPS2,ATAS2,ATGS2,ACNS2,AACS2,ACCS2,ISGSE,VTIS1,ACIS1,
     XACRS2,ATIS2,ATRS2,PERS2,XCHS2,XTKS2,ZCHS2,ZTKS2,L,L1 TK)
      DVP=(VCHSS-VCHS2)/((PCH/PTK)-PRAT)
      PRAT=AMAX1(0.0,AMIN1(1.0,(PCH/PTK)))
C******** CALCULATE DVTK ***************************
      CALL MC(MX,PRAT)
      MY=MX*HYI
      CALL TK((ISHTK,PH2TK,R2 TK,R1 TK,PH1TK,L1 TK,L2 TK,HY,A,E,L,LS)
      ISHAPE=ISHTK
      IF(ISHAPE.EO.0) GO TO 199
      CALL SE(ITYSE,BE SE,DX SE,ZCXSE,XCXSE,DELSE,XCISE,ZCISE,ICLFM,R2 T
     1K,PH2TK,O2IS1,LS,M,N,O,ISGSE)
      CALL CO(SL&CO,XCXSE,ZCXSE,YSG,XCG,SIE,PHE,THE,CC,FF,GG)
      CALL PR(YG PR)
      CALL CL(YGHCL,ICN,PHE,THE,SL&CO,YG PR)
      RHOFM=RHO
      CALL S1(O2IS1,A1 S1,A2 S1,SI S1,CI S1,OXIS1,BEIS1,L1IS1,L2IS1,R1IS
     11,R2IS1,SNIS1,PH2TK,R2 TK,DX SE,BE SE,HY,P1 TK,PH1TK,ICLFM,L1 TK,L
     X2 TK,ITYSE,D,A,E,N,M,VTIS1,ACIS1,LS)
      CALL SP(VTKS2,VCHS2,ACHS2,PH2TK,R2 TK,O2IS1,BE SE,A1 S1,A2 S1,DX S
     1E,SI S1,      ITYSE,YGHCL,HY   ,CI S1,OXIS1,BEIS1,XCISE,ZCISE,L2 T
     2K,L1IS1,L2IS1,R1IS1,R2IS1,DELSE,SNIS1,XCXSE,O,LS,AM,NX,NM,HYI,LX,S
     3M,VCO,R1 TK,AGPS2,ATAS2,ATGS2,ACNS2,AACS2,ACCS2,ISGSE,VTIS1,ACIS1,
     XACRS2,ATIS2,ATRS2,PERS2,XCHS2,XTKS2,ZCHS2,ZTKS2,L,L1 TK)
      DVK=(VTKS2-VTKS)/.01
      VTK=VTKS2
  199 CONTINUE
C          CONVERT RADIANS TO DEGREES
      THETAE=THETAE/RADIAN
      PHIE=PHIE/RADIAN
      DTHETA=DTHETA/RADIAN
      DPHIE=DPHIE/RADIAN
      SIE=SIE/RADIAN
      RETURN END
      SUBROUTINE SE(ITYP,BETA,DELX,ZCX,YCX,DELTA,XCHI,ZCHI,ICALL,R2,PHI2
     X,O2I,LS,M,N,O,ISEG)
C DIVISION OF THE TRUNK INTO SEGMENTS
      REAL LS
      DIMENSION ZCX(32),XCX(32),ITYP(32),DELTA(32),ISEG(32),XCHI(32),ZCH
     XI(32)
      DATA PI/3.14159265/
               NSTOP=32
C IF FIRST CALL,COMPUTE PARTIAL TERMS AND NUMBER SEGMENTS
      IF(ICALL) 30,30,20
   30 RLSM=0.5*LS
C BETA IS CURVED SEGMENT ARC ANGLE
      BETA=PI/2./FLOAT(N)
C DELX IS STRAIGHT SEGMENT LENGTH
      DELX=LS/FLOAT(2*M)
      BETA2=1.33333*SIN(BETA/2.)/BETA
C NUMBERING OF SEGMENTS ACCORDING TO THEIR POSITION IN THE TRUNK
      DO 11 I=1,NSTOP
```

84

```
        IF(I.LE.N)ISEG(I)=1
        IF(I.GT.N.AND.I.LE.N+M)ISEG(I)=2
        IF(I.GT.N+M.AND.I.LE.N+2*M)ISEG(I)=3
        IF(I.GT.N+2*M.AND.I.LE.2*(N+M))ISEG(I)=4
        IF(I.GT.2.*(N+M).AND.I.LE.3.*N+2*M) ISEG(I)=5
        IF(I.GT.3*N+2*M.AND.I.LE.3*(N+M))ISEG(I)=6
        IF(I.GT.3*(N+M).AND.I.LE.3*N+4*M) ISEG(I)=7
        IF(I.GT.3*N+4*M.AND.I.LE.4*(N+M)) ISEG(I)=8
11      CONTINUE
C EVALUATING PROPERTIES OF SEGMENTS
C ITYP=1 FOR CURVED SEGMENT,=0 FOR STRAIGHT SEGMENT
C XCX AND ZCX ARE X AND Z COORDINATES RESP. OF THE SEGMENT CENTER
C XCHI AND ZCHI ARE X AND Z COORDINATES RESP. OF THE CUSHION
C PRESSURE CENTER FOR A SEGMENT,WHEN IT IS OUT OF GROUND CONTACT
C DELTA IS SEGMENT CENTER ANGLE RELATIVE TO CG
20      CONTINUE
        D2=0.5*D+R2*SIN(PHI2)
        DO 10 I=1,NSTOP
        KGO=ISEG(I)
        GO TO (1,2,3,4,5,6,7,8), KGO
C CURVED SEGMENT
C IF NOT INITIAL CALL SKIP CALCULATIONS
1       IF(ICALL) 9,100,9
100     ITYP(I)=1
        DELTA(I)=(FLOAT(I-1)+0.5)*BETA
        COSDEL=COS(DELTA(I))
        XCX(I)=-(RLSH+D2I*COSDEL)
        ZCX(I)=D2I*SIN(DELTA(I))
        XCHI(I)=-(RLSH+D2I*BETA2*COSDEL)
        ZCHI(I)=ZCX(I)*BETA2
        GO TO 9
C STRAIGHT SEGMENT
2       ITYP(I)=0
        XCX(I)=-RLSH+(FLOAT(I-1-N)+0.5)*DELX
        ZCX(I)=D2
        XCHI(I)=XCX(I)
        ZCHI(I)=ZCX(I)*0.5
        GO TO 9
C STRAIGHT SEGMENT
3       ITYP(I)=0
        XCX(I)=(FLOAT(I-N-M-1)+0.5)*DELX
        ZCX(I)=D2
        XCHI(I)=XCX(I)
        ZCHI(I)=ZCX(I)*0.5
        GO TO 9
C CURVED SEGMENT
C IF NOT INITIAL CALL SKIP CALCULATIONS
4       IF(ICALL) 9,400,9
400     DELTA(I)=(FLOAT(I-N-2*M-1)+0.5)*BETA
        SINDEL=SIN(DELTA(I))
        XCX(I)=RLS+D2I*SINDEL
        ZCX(I)=D2I*COS(DELTA(I))
        XCHI(I)=RLSH+D2I*BETA2*SINDEL
        ZCHI(I)=ZCX(I)*BETA2
        GO TO 9
C CURVED SEGMENT
C IF NOT INITIAL CALL SKIP CALCULATIONS
5       IF(ICALL) 9,500,9
500     ITYP(I)=1
        DELTA(I)=(FLOAT(I-2*N-2*M-1)+0.5)*BETA
        COSDEL=COS(DELTA(I))
        XCX(I)=RLSH+D2I*COSDEL
        ZCX(I)=-D2I*SIN(DELTA(I))
        XCHI(I)=RLSH+D2I*COSDEL*BETA2
        ZCHI(I)=ZCX(I)*BETA2
        GO TO 9
```

```
C STRAIGHT SEGMENT
   6      ITYP(I)=0
          XCX(I)=RLSH-(FLOAT(I-3*N-2*M-1)+0.5)*DELX
          ZCX(I)=-D2
          XCHI(I)=XCX(I)
          ZCHI(I)=ZCX(I)*0.5
          GO TO 9
C STRAIGHT SEGMENT
   7      ITYP(I)=0
          XCX(I)=-(FLOAT(I-3*N-3*M-1)+0.5)*DELX
          ZCX(I)=-D2
          XCHI(I)=XCX(I)
          ZCHI(I)=ZCX(I)*0.5
          GO TO 9
C CURVED SEGMENT
C IF NOT INITIAL CALL SKIP CALCULATIONS
   8      IF(ICALL) 9,800,9
  800     ITYP(I)=1
          DELTA(I)=(FLOAT(I-4*N-4*M-1)+0.5)*BETA
          SINDEL=SIN(DELTA(I))
          XCX(I)=-(R_SH+D2I*SINDEL)
          ZCX(I)=-D2I*COS(DELTA(I))
          XCHI(I)=-(RLSH+D2I*SINDEL*BETA2)
          ZCHI(I)=ZCX(I)*BETA2
   9      CONTINUE
  10      CONTINUE
          RETURN
          END
          SUBROUTINE TK(ISHAPE,PHI2,R2,R1,FHI1,L1,L2,HY,A,B,L,LS)
C TRUNK GEOMETRY CALCULATIONS
          REAL L,L1,L2,LS
          RTOL=.1
          IF(HY.LE.0.)) GO TO 111
C**************************************************************************
C ITERATION FOR R2
C COMPUTE INNER RADIUS OF CURVATURE
          R2=SQRT(A*A*0.25+HY*HY)
C
C ITERATION LOOP FOR L2,BU,P1,R2
          DO 102 I=1,50
          PHI2=ABS(ACOS(AMAX1(-1.0,AMIN1(1.0,((R2-HY)/R2)))))
          SINPH2=SIN(PHI2)
C COMPUTE OUTER RADIUS OF CURVATURE
          R1=((A-R2*SINPH2)**2+(B+HY)**2)/(2.*(B+HY))
          PHI1=ABS(ACOS(AMAX1(-1.0,AMIN1(1.0,((R1-HY-B)/R1)))))
          XS=A-R2*SINPH2
          IF (XS.LE.0.0) PHI1=6.2831952-PHI1
          L2=L-PHI1*R1
C R2S IS RESULTANT RADIUS FOR COMPUTED L2 IN ITERATION
          IF(ABS(PHI2).LT.1.0E-2) PHI2=1.0E-2
          R2S=L2/PHI2
C TEST IF TOLERANCE .GT. ERROR
          IF(ABS(R2-R2S).LE.RTOL) GO TO 50
          R2=(R2+R2S)*0.5
  102     CONTINUE
C**************************************************************************
C ITERATED 50 TIMES WITHOUT SUCCESS,ERROR RETURN
  111     CONTINUE
          WRITE(6,9011)
 9011     FORMAT(10X,' INFEASABLE TRUNK GEOMETRY '///)
          ISHAPE=0
          RETURN
C TRUNK OK,RETURN
  50      L1=L-L2
          ISHAPE=1
          RETURN
```

```
      END
      SUBROUTINE S1(D2I,A1,A2,S1,D2D24DI,DXAMAB1,BETAD2I,L1I,L2I,R1I,R2I
     X,SINFHRI,PHI2,R2,DELX,BETA,HY,P1,PHI1,ICALL,L1,L2,ITYP,D,A,E,N,M,V
     XTKI,ACHI,LS)
C INITIAL ASSESSMENT OF AREAS,VOLUMES ASSUMING
C NO GROUND CONTACT
      REAL L1,L2,L1I,L2I,LS
      DIMENSION ITYP(32),ATKI(32),VTKI(32),ACHI(32)
      NSTOP=32      S9=E
C COMPUTE GEOMETRY TERMS
      SINPH2=SIN(PHI2)
      SINPHR=SINPH2*R2
      D2=D/2.+SINPHR
      UD2=DELX*D2
      BCD2=BETA*D2*D2*0.5
      X=B*(A-SINPHR)/(B+HY-P1)
C COMPUTE AREAS OF TRUNK SECTORS
      A1=PHI2/2.0*R2**2
      A2=(R2-HY)/2.0*SINPHR
      A3=PHI1/2.0*R1**2
      A4=X*B/2.0
      A5=(A-SINPHR-X)/2.0*(HY-P1)
      X1=SINPHR-4.0*(SIN(PHI2/2.0))**2*R2/(3.0*PHI2)
      X2=0.66667*SINPHR
      X3=SINPHR+4.0*(SIN(PHI1/2.0))**2*R1/(3.0*PHI1)
      X4=A-0.333333*X
      X5=SINPHR+0.333333*(A-SINPHR-X)
      S=2.0*LS+6.29313*D2
      AA=A1+A3+A5-A2-A4
      AX=A1*X1-A2*X2+A3*X3-A4*X4+A5*X5
      IF(ICALL.GT.0) GO TO 20
C SAVE TRUNK GEOMETRY TERMS FOR END TRUNK CALCULATIONS
      R1I=R1
      R2I=R2
      PHI1I=PHI1
      PHI2I=PHI2
      L1I=L1
      L2I=L2
      A1I=A1
      A2I=A2
      SINPH2I=SINPH2
      SINPHRI=SINPHR
      X1I=X1
      X2I=X2
      A1MA2I=A1-A2
      D2I=D2
      SI=S
      BETAD2I=BETA*D2
      X12=(X1*A1-X2*A2)/A1MA2I
      DXAMA3I=(D*0.5+X12)*A1MA2I*BETA
      L2D2HRI=D2*D2*0.5*BETA
      DD2I=DELX*D2
      BDD2I=BETA*D2*D2*0.5
  20  CONTINUE
C COMPUTE TRUNK SEGMENT AREA,VOLUME,CUSHION AREA
      DO 103 I=1,NSTOP
      IF(ITYP(I).EQ.1)GO TO 112
C STRAIGHT PART OF TRUNK
 131  ATKI(I)=AA
      VTKI(I)=DELX*ATKI(I)
      ACHI(I)=DD2
      GO TO 102
C CURVED PART OF TRUNK
 112  IF(ICALL.GT.0) GO TO 102
      ATKI(I)=AA
      XE=AX/ATKI(I)
```

```
        VTKI(I)=BETA*(D/2.+XE)*ATKI(I)
        ACHI(I)=8032
 102  CONTINUE
 103  CONTINUE
        RETURN SEND
        SUBROUTINE HC(Z,X)
C SUBROUTINE TO CALCULATE POSITIONS OF
C SIDE TRUNK LOBES
C THE POSITION  (EXPRESSED BY HY) DEPENDS ON PRESSURES
C I.E. HY/HYI=F(PCH/PTK)
C FORCE INPUT PRESSURE RATIO BETWEEN 0.0 AND 1.0
        AH0=1.003 $AH1=-.866 $AH2=.328 $AH3=-.463
        X=AMIN1(1.0,AMAX1(0.0,X))
        Z=AH0+AH1*X+AH2*X*X+AH3*X*X*X
        IF(Z.LT.0.1)Z=0.1
        IF (Z.GT.1.0) Z=1.0
        RETURN
        END
        SUBROUTINE CL(YGH,ICLN,PHIE,THETAE,SL4,YG)
        DIMENSION SL4(32 ),YG(32 ),YGH(32 )
        NSTOP=32
C CALCULATION OF TRUNK GROUND CLEARANCE FOR EACH SEGMENT
        ICLNS=ICLN
        COSCOS=COS(PHIE)*COS(THETAE)
C CALCULATE SEGMENT GAP
        DO 161 I=1,NSTOP
        YGH(I)=SL4(I)-YG(I)*COSCOS
C IF NEGATIVE SET GAP TO ZERO
        YGH(I)=AMAX1(YGH(I),0.0)
        IF(YGH(I).LE.0.0) ICLN=ICLN+1
 161  CONTINUE
        ICLN=ICLNS
        RETURN
        END
        SUBROUTINE CO(SL4,XCX,ZCX,YCG,XCG,SIE,PHIE,THETAE,CC,FF,GG)
C THIS SUBROUTINE CALCULATES X AND Z COORDINATES OF THE GROUND
C POINT CORRESPONDING TO EACH SEGMENT, FOR A PARTICULAR ACLS
C ORIENTATION
        DIMENSION SL4(32 ),YCX(32 ),ZCX(32 ),XCG(32 ),ZG(32 )
        NSTOP=32
C CALL EMATRIX FOR SPACIAL TRANSFORMATION
C EMATRIX TRANSFORMS A VECTOR FROM VEHICLE FREAME TO INERTIAL FRAME
C
C
C CALCULATE TRANSCENDENTALS
        CSIE=COS(SIE)
        CPHIE=COS(PHIE)
        CTHETAE=COS(THETAE)
        SSIE=SIN(SIE)
        SPHIE=SIN(PHIE)
        STHETAE=SIN(THETAE)
C
C COMPUTE TRANSLATION MATRIX ELEMENTS
        B11=CSIE*CPHIE+STHETAE*SPHIE*SSIE
        B12=SPHIE*STHETAE
        B13=-SSIE*CPHIE+STHETAE*SPHIE*CSIE
        B21=-SPHIE*CSIE+SSIE*CPHIE*STHETAE
        B22=CPHIE*CTHETAE
        B23=SPHIE*SSIE+CSIE*CPHIE*STHETAE
        B31=SSIE*CTHETAE
        B32=-STHETAE
        B33=CSIE*CTHETAE
C
C DO LOOP OF ALL SEGMENTS TO GROUND POSITION
        DO 104 I=1,NSTOP
        XCXCC=(XCX(I)-CC)
```

```
      ZCXFF=(ZCX(I)-FF)
C
C CALCULATE VECTOR DA FOR SEGMENT
      SL4(I)=(YCG+XCXCC*B12+ZCXFF*B32)/B22-GG
      SL4GG=(SL4(I)+GG)
C
C CALCULATE X-GROUND COORDINATE
      XG(I)=XCXCC*B11-SL4GG*B21+ZCXFF*B31+XCG
C
C CALCULATE Z-GROUND COORDINATE
      ZG(I)=XCXCC*B13-SL4GG*B23+ZCXFF*B33
 104  CONTINUE
      RETURN
      END
      SUBROUTINE PR(YG)
C USER SPECIFIED GROUND PROFILE.
C ELEVATION YG(I) IS EXPRESSED AS A FUNCTION OF X AND Z COORDINATRES
C OF GROUND POINT I,I.E, XG(I) AND ZG(I)
      DIMENSION YG(32 )
      NSTOP=32
      DO 105 I=1,NSTOP
C SET FOR FLAT TERRAIN
      YG(I)=0.
 105  CONTINUE
      RETURN
      END
      SUBROUTINE SP(VTK,VCH,ACH,PHI2,R2,D2I,BETA,A1,A2,DELX,SI,ITYP,YGH,
     XHY,D2D2HES,DXAMA9,BETAD2I,XCMI,ZCMI,L2,L1I,L2I,F1I,R2I,DELTA,SINP
     XHRI,XCK,D,LS,AH,NX,NH,HYI,LX,SH,VCHO,R1,AGAP,ATKAT,ATKCH,ATKCN,ATK
     XATC,ATKCHC,ISEG,VTKI,ACHI,ACHP,ATKCNI,ATKCNR,PERI,XCH,XTK,ZCH,ZTK,
     XL,L1)
C CALCULATION OF AREAS AND VOLUMES ASSOCIATED WITH ACLS,KNOWING ITS
C ORIENTATION
      REAL L2,LS,LX,L1I,L2I,L,L1
      DIMENSION VTKRB(32 ),VTKRA(32 ),PERI(32 ),XCH(32 ),ZCH(
     X32 ),ATKCNI(32 ),ATKCNR(32 ),ATKATI(32 ),ATKATR(32 ),VCHI(32 ),AGA
     XPI(32 ),AGAPR(32 ),XTK(32 ),ZTK(32 ),ATKR(32 ),ACHI(32),XCHI(32 ),
     XZCHI(32 ),YGH(32 ),ISEG( 32),VTKI( 32),XCY(32),ITYP(32),DELTA(32),
     XACHR(32),VCHR(32),VTKR(32),ATKCHR(32),ATKCHI(32)
      NSTOP=32                                $PI=3.141592653
      ATOTAL=.6
C COMPUTE PARTIAL TERMS
      SINPH2=SIN(PHI2)
      SINPHR=SINPH2*R2
      D2=D*0.5+SINPHR
      D2ISQ=D2I*D2I
      A1MA2=A1-A2
      BETA2=1.33333*SIN(BETA/2.)/BETA
      RLSH=LS*0.50
      ADS=AH*DELX/SI
      ABDSI=AH*BETA*D2I/SI
      RNN=FLOAT(NX*NH)
C*********************************************************************
C PART I I VALUE OF VCH AND AGAP
C*********************************************************************
      DO 17 I=1,NSTOP
C TEST FOR TRUNK SEGMENT, WHETHER CURVED OR STRAIGHT
      IF(ITYP(I).EQ.1)GO TO 11
C
C STRAIGHT PART OF TRUNK
C
C CALCULATE CUSHION SEGMENT INITIAL VOLUME
  13  VCHI(I)=(YGH(I)*D2-A1MA2)*DELX
C CALCULATE SEGMENT GAP AREA
      AGAPI(I)=(YGH(I)-HY)*DELX
      GO TO 10
```

89

```
C
C CURVED PART OF TRUNK
C
   11   VCHI(I)=YGH(I)*D2D2H8I-DXAHABI
        ACAPI(I)=(YGH(I)-HVI)*DETA)2I
C***********************************************************************
C PART 2 R VALUE CALCULATIONS
C***********************************************************************
C
C TEST FOR GROUND CONTACT AT EACH SEGMENT
   10   CONTINUE
C FORCE VOLUME AREAS .GE.0
        VCHI(I)=AMAX1(0.0,VCHI(I))
        ACAPI(I)=AMAX1(0.0,ACAPI(I))
C TEST SEGMENT FOR CONTACT
        IF(ITYP(I).EQ.1.AND.YGH(I).LE.HVI) GO TO 14
        IF(ITYP(I).EQ.0.AND.YGH(I).LE.HV) GO TO 23
C
C NO GROUND CONTACT
C SET CONTACT AND REMOVE TERMS TO ZERO
        ATKR(I)=0.0
        ACHR(I)=0.0
        VTKR(I)=0.0
        VCHR(I)=0.0
        AGAPH(I)=0.0
        ATKCNI(I)=0.0
        ATKCNR(I)=0.0
        ATKCHR(I)=0.0
        ATKATR(I)=0.0
        PERI(I)=0.0
C SET DISTANCES X,Y TO FREE TRUNK VALUES
        XCH(I)=XCHI(I)
        ZCH(I)=ZCHI(I)
        ZTK(I)=ZCH(I)
        XTK(I)=XCH(I)
C COMPUTE TRUNK-CUSHION-ATMOSPHERE BLEED AREAS
        IF(ITYP(I)) 16,16,18
   16   CONTINUE
C NO CONTACT STRAIGHT SECTIONS
        ATKCHI(I)=FLOAT(IFIX((L2-LX)/SH+1.0)*NH)*ADS
        ATKATI(I)=INN*ADS-ATKCHI(I)
        GO TO 17
   18   CONTINUE
C NO CONTACT CURVED SECTIONS
        ATKCHI(I)=FLOAT(IFIX((L2I-LX)/S4+1.0)*NH)*ABDSI
        ATKATI(I)=INN*ADSI-ATKCHI(I)
        GO TO 17
C***********************************************************************
C
C TRUNK GROUND CONTACT
C
C CURVED PART OF TRUNK
C CALCULATE DEFORMATION ANGLES FOR SEGMENT
   14   PHI3=ACOS((R2I-(HVI-YGH(I)))/R2I)
        PHI4=ACOS((R1I-(HVI-YGH(I)))/R1I)
        SINPH3=SIN(PHI3)
        SINPH4=SIN(PHI4)
C COMPUTE PARTIAL TERMS
        DRSP=(D2I-R2I*SINPH3)
        DRSP2=DRSP*DRSP
        COSDEL=COS(DELTA(I))
        SINDEL=SIN(DELTA(I))
        DFDRSH=D2TA2*DRSP*SINDEL
        DFDRCS=DET12*DRSP*COSDEL
C COMPUTE REMOVAL SECTORS
        A6=R2I*R2I*PHI3*0.5
```

```
      A7=(R2I-HYI*YGH(I))*0.5*R2I*SINPH3
      A6MA7=A6-A7
      A8=R1I*R1I*PHI4*0.5
      A9=(R1I-HYI*YGH(I))*0.5*R1I*SINPH4
      A10=A9
      A11=A8
C COMPUTE SECTOR CENTROIDS
      X6=SINPHRI-1.333333*(SIN(PHI3*0.5)**2)*R2I/PHI3
      X7=SINPHRI-0.333333*R2I*SINPH3
      X8=SINPHRI+1.333333*(SIN(PHI4*0.5)**2)*R1I/PHI4
      X9=SINPHRI+0.333333*R1I*SINPH4
      X10=X9
      X11=X8
      PII2=PI*0.5
      IF(PHI4.LT.PII2) GO TO 50
C IF PHI4 GREATER THAN 90 DEGREES, SET TO 90 DEGREES
      PHI4=PII2
      SINPH4=SIN(PHI4)
      A10=(R1I-HYI*YGH(I))*R1I
      X10=SINPHRI+0.5*R1I
      A11=R1I*R1I*PHI4*0.5
      X11=SINPHR+1.333333*(SIN(PHI4*0.5)**2)*R1I/PHI4
   50 CONTINUE
C COMPUTE TRUNK AREA CHANGE
      ATKR(I)=A6MA7+A8-A9
      ATKRB(I)=A6MA7+A11-A10
      XER=(A6*X6-A7*X7+A8*X8-A9*X9)/ATKR(I)
      XERB=(A6*X6-A7*X7+A11*X11-A10*X10)/ATKRB(I)
C COMPUTE TRUNK VOLUME CHANGE
      VTKRA(I)=BETA*(D**0.5+XER)*ATKR(I)
      VTKRB(I)=ATKRB(I)*BETA*(D*0.5+XERB)
      VTKR(I)=2.*VTKRA(I)-VTKRB(I)
      XCR=(A6*X6-A7*X7)/A6MA7
C COMPUTE TRUNK EXIT AREAS
      ATKCHI(I)=FLOAT(IFIX((L2I-LY-R2I*PHI3)/SH+1.0)*NH)*ADOSI
      ATKATI(I)=FLOAT(IFIX((L1I-L+LY*FLOAT(NX-1)*SH-R1I*PHI4)/SH+1.0)*NH
     1)*ADOSI
      ATKCHR(I)=FLOAT(IFIX((L2I-LY)/SH+1.0)*NH)*ADOSI-ATKCHI(I)
      ATKATR(I)=NH*ADOSI-ATKCHI(I)-ATKATI(I)-ATKCHR(I)
      PERI(I)=BETA*(DRSP+D2I+R1I*SINPH4)
C COMPUTE CONTACT PERIMETER
      ATKCNI(I)=BETA*0.5*(D2ISQ-DRS*2)
C COMPUTE TRUNK CONTACT AREA
      ATKCNA(I)=BETA*0.5*((D2I+R1I*SINPH4)**2-D2ISQ)
      ACHR(I)=ATKCNI(I)
C COMPUTE CUSHION VOLUME CHANGE
      VCHR(I)=BETA*A6MA7*(D*0.5+XCR)
C COMPUTE GAP AREA CHANGE
      AGAPR(I)=A3API(I)
C DISTANCE OF SEGMENT PRESSURE CENTERS FROM CUSHION CENTER
   29 RR=D2I+R1I*SINPH4
      RR1=C2I-R2I*SINPH3
      XY2=1.333333*SIN(BETA*0.5)/BETA*(RR**3-RR1**3)/(RR*RR-RR1*RR1)
      KGO=ISEG(I)
      GO TO (61,23,23,64,65,23,23,66),KGO
   61 XCH(I)=-RLSH-BEDRCS
      ZCH(I)=DSDRSN
      XTK(I)=-RL1H-XY2*COSDEL
      ZTK(I)=XY2*SINDEL
      GO TO 17
   64 XCH(I)=RLSH+BEDRSN
      ZCH(I)=BEDRCS
      XTK(I)=RL1H+XY2*SINDEL
      ZTK(I)=XY2*COSDEL
      GO TO 17
   65 XCH(I)=RLSH+BEDRCS
```

```
      ZCH(I)=-BEDRSN
      XTK(I)=RLS4+XX2*COSDEL
      ZTK(I)=-XX2*SINDEL
      GO TO 17
  68  XCH(I)=-RLSH-BEDRSN
      ZCH(I)=-BEDRCS
      XTK(I)=-RLSH-XX2*SINDEL
      ZTK(I)=-XX2*COSDEL
      GO TO 17
C********************************************************************************
C
C TRUNK GROUND CONTACT
C STRAIGHT PART OF TRUNK
  23  CONTINUE
C COMPUTE DEFORMATION ANGLES
      RHY=((R2-(HY-YGH(I)))/R2)
      PHI3=ACOS(AMAX1(-1.0,AMIN1(1.0,RHY)))
      RHY=((R1-(HY-YGH(I)))/R1)
      PHI4=ACOS(AMAX1(-1.0,AMIN1(1.0,RHY)))
C DO TRANSCENDENTALS ONLY ONCE
      SINPH3=SIN(PHI3)
      SINPH4=SIN(PHI4)
C COMPUTE PARTIAL TERMS
      DRSP=(D2-R2*SINPH3)
      DRSP2=DRSP*DRSP
      COSDEL=COS(DELTA(I))
      SINDEL=SIN(DELTA(I))
      BEDRSN=BETA2*DRSP*SINDEL
      BEDRCS=BETA2*DRSP*COSDEL
C COMPUTE REMOVAL SECTORS
      A6=R2*R2*PHI3*0.5
      A7=(R2-HY +YGH(I))*0.5*R2*SINPH3
      A6MA7=A6-A7
      A8=R1*R1*PHI4*0.5
      A9=(R1-HY +YGH(I))*0.5*R1*SINPH4
      A10=A9
      A11=A8
C COMPUTE SECTOR CENTROIDS
      X6=SINPH3-1.333333*(SIN(PHI3*0.5)**2)*R2/PHI3
      X7=SINPH3-0.333333*R2*SINPH3
      X8=SINPH4+1.3333333*(SIN(PHI4*0.5)**2)*R1/PHI4
      X9=SINPH4+0.3333333*R1*SINPH4
      X10=X9
      X11=X8
      PII2=PI*0.5
      IF(PHI4.LT.PII2) GO TO 70
C IF PHI4 IS GREATER THAN 90 DEGREES, SET TO 90 DEGREES
      PHI4=PII2
      SINPH4=SIN(PHI4)
      A10=(R1-HY+YGH(I))*R1
      X10=SINPH4+0.5*R1
      A11=PI*R1*PHI4*0.5
      X11=SINPH4+1.3333333*(SIN(PHI4*0.5)**2)*R1/PHI4
  70  CONTINUE
C COMPUTE TRUNK AREA CHANGE
      ATKR(I)=A6MA7+A8-A9
      ATKR2(I)=A6MA7+A11-A10
C COMPUTE TRUNK VOLUME CHANGE
      VTKRA(I)=ATKR(I)*DELX
      VTKRB(I)=ATKR2(I)*DELX
      VTKR(I)=2.*VTKRA(I)-VTKRB(I)
C COMPUTE CUSHION VOLUME CHANGE
      VCHR(I)=-DELX*A6MA7
C COMPUTE TRUNK EXIT AREAS
      ATKATI(I)=FLOAT(IFIX((L1-L+LX+FLOAT(NX-1)*SH-R1*PHI4)/SH+1.0)*NH)
     1*ADS
```

92

```
      ATKCHI(I)=FLOAT(IFIX((L2-LX-R2*SINH3)/SH+1.)*NH)*ADS
      ATKCHR(I)=FLOAT(IFIX((L2-LX)/SH+1.0)*NH)*ADS-ATKCHI(I)
      ATKATR(I)=RMN*ADS-ATKCHI(I)-ATKATI(I)-ATKCHR(I)
      PERI(I)=2.*DELX
C COMPUTE TRUNK CONTACT PERIMETER
C COMPUTE TRUNK CONTACT AREA
      ATKCNI(I)=R2*SINPH3*CELX
      ATKCNR(I)=R1*SINPH4*CELX
C COMPUTE GAP AREA CHANGE
      ACHR(I)=ATKCNI(I)
      AGAPR(I)=AGAPI(I)
      KGO=ISEG(I)
C COMPUTE SEGMENT CONTACT CENTER OF PRESSURE FOR CUSHION AND TRUNK
      GO TO (17,12,62,17,17,66,66,17),KGO
 62   XCH(I)=XCX(I)
      ZCH(I)=0.5*(D2-R2*SINPH3)
      XTK(I)=XCX(I)
      ZTK(I)=D2+0.5*(R1*SINPH4-R2*SINPH3)
      GO TO 17
 66   XCH(I)=XCX(I)
      ZCH(I)=-0.5*(D2-R2*SINPH3)
      XTK(I)=XCX(I)
      ZTK(I)=-(D2+0.5*(R1*SINPH4-R2*SINPH3))
 17   CONTINUE
C*************************************************************
C PART 3 SUMMATION OF SEGMENT AREAS VOLUMES
C*************************************************************
C
C SET TOTAL AREA AND VOLUMES TO ZERO
      ATKCN=0.0
      VTK=0.0
      ACH=0.0
      ATKCH=0.0
      ATKAT=0.0
      VCH=0.0
      AGAP=0.0
      ATKATC=0.
      ATKCHC=0.
C LOOP ON SEGMENTS TO FIND TOTALS OF AREAS AND VOLUMES.
      DO 30 I=1,NSTOP
      VTK=VTK+ (VTKI(I)-VTKP(I))
      ACH=ACH+ (ACHI(I)-ACHR(I))
      ATKCH=ATKCH+ATKCHI(I)
      ATKAT=ATKAT+ATKATI(I)
      VCH=VCH+ (VCHI(I)-VCHP(I))
      ATKCN=ATKCN+ATKCNI(I)+ATKCNR(I)
      AGAP=AGAP+ (AGAPI(I)-AGAPR(I))
      ATKATC=ATKATC+ATKATR(I)
      ATKCHC=ATKCHC+ATKCHR(I)
 30   CONTINUE
      AGAP=AMAX1(AGAP,0.0)
      VTK=AMAX1(0.0,VTK)
      VCH=AMAX1(0.0,(VCH+VCHO))
      VCH=AMAX1(0.0,VCH)
      ATKCH=AMAX1(0.000,ATKCH)
      ATKAT=AMAX1(0.000,ATKAT)
      ACH=AMAX1(0.0,ACH)
      ATKATC=AMAX1(0.0,ATKATC)
      ATKCHC=AMAX1(0.0,ATKCHC)
C FORCE SUM OF NOZZLE AREAS TO BE EQUAL TO TOTAL NOZZLE AREA
      SUM=ATKAT+ATKCH+ATKATC+ATKCHC
      ATKCH=ATKCH/SUM*ATOTAL  ATKAT=ATKAT/SUM*ATOTAL
      ATKCHC=ATKCHC/SUM*ATOTAL  ATKATC=ATKATC/SUM*ATOTAL
      RETURN
      END
      SUBROUTINE ST(FY,TZ,TX,DERY,IPP,PPLM,VPLM,VTK,OFANX,OVTK,PTK,OVCH,
```

```
      XYCG,CVCMP,PCH,VCH,SINKPT,PHIE,DPHI ,THETAE,DTHETA,CKK,PAT,GG,HYI,G
      XEC,MASS,RPM,                              SIE,RHO,AGAP,ACM,ATK
      XAT,ATKCH,ATKCN,ATKATC,ATKCHC,CAF,CENFX,CGAP,         ACHR,ATKCNI,ATKCN
      CR,PERI,XCH,ZCH,XTK,ZTK,ACHI,YGH,CPLTK,QTKCH,QTKAT,OCHAT)
C DYNAMIC FAN VERSION FOR FMA.
C STATE EQUATIONS FOR THE DYNAMIC SYSTEM
      REAL MASS
C FOLLOWING SUBROUTINES ARE CALLED TO UPDATE VALUES OF
C FORCES,TORCUES AND FLOWS, GIVEN THE NEW VALUES OF THE
C STATE VARIABLES
      DIMENSION DERY(13),ACHI(32),ACHR(32),ATKCNI(32),ATKCNR(32),PERI(32
     X),XCH(32),ZCH(32),XTK(32),ZTK(32),YGH(32)
      CC=-1.173AATFN=.796         SCPT=.6 TCTA=.4         SQVENT=0.
              CTC=.4 SFF=0.
              HDC=1.            SPHA=155.           SU=0.03
                        APLTK=.698  SDAHPC=3.2            SAIFAN=.072
                        CENFZ=0.    INSTOP=32
C SUBROUTINE TO FIND FLOW AND PRESSURE VALUES DURING DYNAMIC SIMULATION
      TIRHO=2.0/RHO
C PLEMUN TO TRUNK FLOW
      SIGN=1.0
      IF((PPLM-PTK).LT.0.0) SIGN=-1.0
      OPLTK=SIGN*CPT*APLTK*SORT(ABS(TIFHO*(PPLM-PTK)))
C TRUNK TO CUSHION FLOW
      SIGN=1.
      IF((PTK-PCH).LT.0.) SIGN=-1.
      QTKCH=SIGN*CTC*SORT(ABS(TIRHO*(PTK-PCH)))*(ATKCH+0.66667*ATKCHC)
C TRUNK TO ATMOSPHERE FLOW
      SIGN=1.0
      IF(PTK.LT.0.0)SIGN=-1.
      QTKAT=SIGN*CTA*SORT(TIRHO*ABS(PTK))*(ATKAT+0.66667*ATKATC)
C CUSHION TO ATMOSPHERE FLOW
      SIGN=1.0
      IF(PCH.LT.0.0) SIGN=-1.0
      QCHAT=AGAP*CGAP*SORT(TIRHO*ABS(PCH))*SIGN
C FORCES AND TORQUES ASSOCIATED WITH A PARTICULAR ACLS ORIENTATION
C ARE CALCULATED
C CALCULATE TRANSCENDENTALS ONLY ONCE
      CSSCS=COS(PHIE)*SIN(THETAE)*SIN(SIE)-COS(SIE)*SIN(PHIE)
      CPCT=COS(PHIE)*COS(THETAE)
C CLEAR TOTAL FORCES AND TORQUES TO ZERO
      FORCT=0.0
      TTPX=0.0
      TTPZ=0.0
      TCPX=0.0
      TCPZ=0.0
      TORFZ=0.0
      TOROTX=0.0
      TOROTZ=0.0 SFORCEY=0. STORQUEX=0. STORQUEZ=0.
C FORCES AND TORQUES INDEPENDENT OF SEGMENTS INDIVIDUALLY
C HEAVE FORCES CUSHION AND TRUNK
      FCP=PCH*ACH
      FTP=PTK*ATKCN
C COMPUTE VELOCITY FOR DRAG FORCE
      V=VELX*CSSCS+SINKRT*CPCT
      SIGN=1.
      IF(V.GT.0.0)SIGN=-1.
C HEAVE DRAG FORCE
      FDF=0.5*HDC*PHA*RHO*V*V*SIGN
C DRAG TORQUE
      TDFZ=FCF*CENFX
      TDFX=-FDF*CENFZ
C FORCES AND TORQUES DEPENDENT ON SEGMENTS INDIVIDUALLY
C SUM INDIVIDUAL SEGMENTS TO FIND TOTALS
      DO 101 I=1,NSTOP
C CUSHION PRESSURE TORQUES
```

94

```
      TCPZ=TCPZ+(XCH(I)-CC)*PCH*(ACHI(I)-ACHR(I))
      TCPX=TCPX-(ZCH(I)-FF)*PCH*(ACHI(I)-ACHR(I))
      TTPZ=TTPZ+(XTK(I)-CC)*(PTK*(ATKCNI(I)+ATKCNR(I)))
      TTPX=TTPX-(ZTK(I)-FF)*(PTK*(ATKCNI(I)+ATKCNR(I)))
      IF((ATKCNI(I).GT.0.).OR.(ATKCNR(I).GT.0.)) GO TO 111
      GO TO 101
111   VELT=           SINKRT*CPCT*OPHI*(XTK(I)-CC)+OTHETA*(ZTK(I)-FF)
      FCPC=-VELT*DAMPC*PERI(I)
      FORCT=FORCT+FORD
      TOROTZ=TOROTZ+(XTK(I)-CC)*FORD
      TOROTX=TOROTX-(ZTK(I)-FF)*FORD
      IF(VELX.EQ.0.0) GO TO 101
      TORFZ=TORFZ-(YCG*CPCT* *PTK*(ATKCNI(I)+ATKCNR(I)))*U
101   CONTINUE
C CUMMATION OF FORCE AND TORQUE COMPONENTS
C TOTAL HEAVE FORCE
      FORCEY=(FCP+FTP+FORCT+FOFI*CPCT
      FY=AMAX1(FORCEY,0.)
C TOTAL TORQUE X AXIS
      TORQUEX=TCPX+TTPX+TOROTX+TOFX
      TX=TORQUEX
C TOTAL TORQUE Z AXIS
      TORQUEZ=TCPZ+TTPZ+TOROTZ+TOFZ+TORFZ
      TZ=TORQUEZ
C STATE EQUATIONS
C***THE STATE VARIABLES***
C 1)PFLM..FLEMUN PRESSURE (GAGE)
C 2)PCM..CUSHION PRESSURE (GAGE)
C 3)PTK..TRUNK PRESSURE (GAGE)
C 4)SINKRT..VERTICAL SINK RATE, POSITIVE UPWARDS
C 5)YCG..CG ELEVATION
C 6)OPHI..PITCH RATE,VEHICLE FRAME
C 7)OTHETA..ROLL RATE, VEHICLE FRAME
C 8)THETAE..EULERIAN ROLL ANGLE
C 9)PHIE..EULERIAN PITCH ANGLE
C 10)SIE..EULERIAN YAW ANGLE (APPROX. ZERO)
C 11)XV..DISPLN OF PRESSURE RELIEF VALVE
C 12)VV..VELOCITY OF PRESSURE RELIEF VALVE
C 13)QFANX..FAN AIR INERTANCE FLOW
      DERY(1)=(CKK*(PFLM+PAT)/VFLM)*(QFANX-QPLTK)
      DERY(3)=(CKK*(PTK+PAT)/VTK)*(QPLTK-QTKCH-QTKAT-QVTK)
C CUSHION FLOW ABOVE GROUND EFFECT TRANSITION ZONE
      QCHFT=QPLC4+QTKCH-QVCM
C CALCULATE GROUND EFFECT TRANSITION ZONE
      TBOUND=GG*HYI*(1.+GSC)
      BBOUND=GG*HYI
C DETERMINE IF ACLS IN TRANSITION ZONE
      IF(YCG.GT.TBOUND)GO TO 13
      IF(YCG.GT.BBOUND) GO TO 14
      GO TO 16
C
C ABOVE TRANSITION ZONE
13    QCHAT=QCHFT
      IFLAG=0
      IO=0
      NO=0
      GO TO 15
C
C IN TRANSITION ZONE
14    IFLAG=1
      NO=100
      IO=IFIX(ABS((TBOUND-YCG)/(TBOUND-BBOUND)*FLOAT(NO)))
      IF(IO.GT.NO)IO=NO
      GO TO 17
C
C IN GROUND EFFECT ZONE
```

95

```
16    NO=1
      IO=1
      IFLAG=2
C COMPUTE CUSHION TO ATMOSPHERE FLOW
17    QCHAT=FLOAT(NO-IO)/FLOAT(NO)*QCHFT+FLOAT(IO)/FLOAT(NO)*QCHAT
C CUSHION PRESSURE DERIVATIVE
45    DERY(2)=(IOPLCH+QTKCH-CCHAT-DVCH+CVCHF+PCH*DERY(3)/(PTK*PTK))/
     1(VCH/(CKK*(PCH+PAT))+DVCHP/PTK)
C CUSHION PRESSURE IS ZERO ABOVE TRANSITION ZONE
      IF(IFLAG.EQ.0.0) PCH=0.0
66    RETURN
      END
PARAMETER VALUES=IO1AV=0
      UMAX=20.
      MSS=77.5                                                    CC=-1.17
      GG= 1.5   ,FF=0. ,PHA=155. ,HOC=1. ,LS=4.125 ,D=.417 -A=.695
      E=.524,L=5.17 ,HYI=1.00 ,              AH=3.4E-4 ,SH=.0833 ,LX=0.60
      AIF=.072
                APC=0. ,APT=.698 ,APA=0. ,AAT=.796         ,VCD=0.
      DPV=8,                        FAT=2116.8 ,TEM=70.
                        ,CKK=1.4 ,CPA=0. ,CAF=.5 ,CPC=0. ,CP7=.6 ,CTC=.4
      CTA=.4 ,CGP=.5 ,GEC=.1 ,    CFX= 1.17 ,CFZ=0. ,OPC=3.2
XA LO=0.  ,XU LO=0.   ,ZA LO=0.  ,HALLO=0.  ,HU LO=0.   ,XP1LO=-.2
                      Y9OLD=0.   ,YB LO=0.   ,YDALD=0.   ,L3OLD=0.
LB LO=0.  ,NBOLO=0.   ,N3 LC=0.   ,NDALD=0.  ,RUOLD=1.   ,B LO=19.
TCOEN=6.4 ,THREN=2353. ,XO FN=-6.1,GAXEN=1.   ,GAZEN=0.   ,PO TF=158.73,
P1 TF=17.46,ZO TF=0.   ,Z1 TF=158.73
                                ,ZO TF 2=158.73
Z1 TF 2=0.,PO TF 2=153.73,P1 TF 2=17.46,
GKIII 3=1.                ,GKLIT 3=1.
C1 MC 1=1.2,C2 MC 1=3.75,C3 MC 1=2.5,C4 MC 1=0.,GKIIT 7=1.,GKLIT 7=1.
GKIIT 6=-1.,GKLIT 8=1.,C1 MC 2=1.54,C2 MC 2=5.75,C3 MC 2=2.5,C4 MC 2=0.,
GKIIT 9=1.,GKLIT 9=1. ,GKIIT10=-1.,GKLIT10=1. ,ALSAV=0.   ,S AV=76.
UW AV=0. ,VW AV=-0.   ,WW AV=0.   ,PW AV=0.   ,QW1AV=0.   ,RW1AV=0.
MA1LO=77.5,C LC=4.    ,GKLIT 1=1. ,GKIIT 1=1. ,IXXSO=2414.,IYYSO=1840. ,
IZZSO=4082.,IXZSO=-203._ ,ZO FN=0._ ,ZU LO=0.
      FY1S3=0.  ,FY2S3=0.  ,T22S3=0.  ,FX2S3=0.  ,TX1S3=0.  ,TZ1S3=0. ,
      FX3S3=0.  ,FY3S3=0.  ,F23S3=0.
                X0 LO=-99.692,ZADLO=-.12366,YP LO=-.035692,ZO LO=-8.0257,
HADLO=-.75699,YR LO=.12081,LP LO=-113.74,XOELO=-.065052,MO LO=-175.86,
YORLO=350.17,LR LO=-15.116,NP LO=-11.851,ZO LO=-10.967,ZOELO=-15.562,
LORLO=607.,NR LO=100.93,MO LO=13.725,MOELO=-865.13,LOALC=-3.6745,
NORLO=119.
INITIAL CONDITIONS=
PPLFH=137.93,PTKFH=126.06,PCHFH=0.    ,TH EN=1515.6,U SO=17.033,
V SO=6.5235,W SO=0.     ,P SO=0.     ,Q SO=0.,0     R SO=0.
ROLSO=0.    ,PITSO=-1.0   ,YAWSO=0.     ,ALTSO=2.6  0,XI TF=0.
X2 TF=0.    ,X2 IT 7=0.     ,X2 IT 9=0.     ,X2 IT 3=0.
X2 IT 1=0.,XI TF 2=0.,X2 TF 2=0.,X2 IT 9=0.,X2 IT10=0.
  PRINT CONTROL=.,TINJ=0.5 ,TMAX=10.,OUTRATE=1   ,PRATE= 1,SIMULATE
```

Vita

Edward Arthur Kenney was born 18 July 1948 in London, Ontario, Canada to James A. and Evelyn V. Kenney. After graduating from G. A. Wheable Secondary School in 1967, he entered the Royal Military College (RMC) in Kingston, Ontario. He graduated from RMC in 1971 with the degree of Bachelor of Science in Electrical Engineering, and a commission in the Canadian Armed Forces. After graduating from the Primary Flying School and attending the Flying Training School at CFB Moose-jaw, Saskatchewan, he reclassified to be an Aerospace Engineer. Subsequent tours of duty included CFB Shearwater, Nova Scotia, as the Deputy Maintenance Records Officer and Heavy Maintenance Repair Officer; H.M.C.S. Preserver as the Fleet Air Maintenance Officer; and National Defence Headquarters, Ottawa, in the Directorate of Avionics and Armament Subsystems Engineering. Capt Kenney was assigned to the United States Air Force Institute of Technology in June 1976 in the Graduate Guidance and Control Program.

Mailing Address: National Defence Headquarters

Ottawa, Ontario Canada

K1A OK2

Attn: DPCO/AERE

SECURITY CLASSIFICATION OF THIS PAGE *(When Data Entered)*

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
AFIT/GE/EE/77D-43		

4. TITLE *(and Subtitle)*	5. TYPE OF REPORT & PERIOD COVERED
The Design and Simulation of a Takeoff Stabilization System for an Aircraft with an Air Cushion Landing System	Master's thesis
	6. PERFORMING ORG. REPORT NUMBER

7. AUTHOR(s)	8. CONTRACT OR GRANT NUMBER(s)
Edward A. Kenney	

9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Air Force Institute of Technology (AFIT/EN) Wright-Patterson AFB, Ohio 45433	

11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
Vehicle Equipment Division, Mechanical Branch, (FEMB), Air Force Flight Dynamics Laboratory, Wright-Patterson AFB, Ohio 45433	Dec 77
	13. NUMBER OF PAGES
	117

14. MONITORING AGENCY NAME & ADDRESS *(if different from Controlling Office)*	15. SECURITY CLASS. *(of this report)*
	Unclassified
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT *(of this Report)*

Approved for public release; distribution unlimited

17. DISTRIBUTION STATEMENT *(of the abstract entered in Block 20, if different from Report)*

18. SUPPLEMENTARY NOTES

Approved for public release; IAW AFR190-17

JERRAL F. GUESS, Captain, USAF
Director of Information

19. KEY WORDS *(Continue on reverse side if necessary and identify by block number)*

ACLS	EASY
SAS	ACTS
Coanda Effect	
Thrust Vector Device	
Aircraft	

20. ABSTRACT *(Continue on reverse side if necessary and identify by block number)*

The inherent instability in pitch and roll associated with an Air Cushion Landing System (ACLS) aircraft at low airspeeds was investigated, and a means to aid control in pitch and roll was developed. The control system required the use of vertical wing tip thrusters which provided thrust up or down depending on the control signal (similar to space vehicle thrusters). These thrusters could be activated alternately to control roll angle and roll rate with the use of a bang-bang optimal controller.

DD FORM 1473   EDITION OF 1 NOV 65 IS OBSOLETE

As well, the thrusters would be set forward of the aircraft center of gravity and could be activated in tandum to aid in pitch control.

The Jindivik Remotely Piloted Vehicle, an Australian target drone, was fitted with an ACLS and taxi tests showed the instability and need for a stabilization system. Subsequent use of Jindivik wind tunnel and taxi test data served as the basis for the development of the roll/pitch control system presented in this paper. Due to computational problems with the air cushion model of the computer program, the controller designs could not be completely verified; but expected trends in pitch, roll, and yaw control were shown.